

© 2013 American Foundry Society

Meets the Requirements of OSHA Standard 29 CFR 1910.1200 Hazard Communication and EPA Supplier Notification Requirements under Section 313 of the Emergency Planning and Community Right-to-Know Act. SAFETY DATA SHEET (SDS)

GRAY IRON CASTINGS SDS SC-000-041 Rev. 12

DATE ISSUED

10/13

SECTION 1—PRODUCT IDENTIFICATION & COMPANY INFORMATION

PRODUCT NAME

GRAY IRON CASTINGS

OTHER DESIGNATIONS: ASTM (American Society for Testing & Materials) Specification No's., (ACI (Alloy Casting Institute) Alloy Designations—Grades)

ASTM: A48, A74, A126, A159, A278, A319, A667, A748, A823, A942

PRODUCT IDENTIFICATION (Label Identifier)

Gray Iron

| MANUFACTURER'S NAME | STREET ADDRESS |
|---|--------------------------------|
| Neenah Foundry Company | 2121 Brooks St. |
| EMERGENCY TELEPHONE NO. CHEMTREC: (800) 424-9300 | MAILING ADDRESS |
| TELEPHONE NO. | CITY, STATE, ZIP CODE, COUNTRY |
| 920.729.3679 or 920.729.3850 | Neenah, WI 54956 USA |
| FAX NO. | E-MAIL ADDRESS/WEBSITE |

RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Solid casting; no restrictions

SECTION 2—HAZARD IDENTIFICATION

CLASSIFICATION

Castings are metallic articles that do not present hazards in their original form.

OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 for further information.

| SECTION 3—COMPOSITION/II | NFORMATION ON INGREDIE | NTS. |
|-----------------------------------|------------------------|------------|
| CHEMICAL NAME/COMMON NAME/SYNONYM | Wt % | CAS NUMBER |
| Carbon (C) | 2.5-4.0 | 7440-44-0 |
| Chromium (Cr) | 0.01-1.5 | 7440-47-3 |
| Copper (Cu) | 0.01–1.00 | 7440-50-8 |
| Iron (Fe) | 86.3-96.2 | 7439-89-6 |
| Manganese (Mn) | 0.2-1.1 | 7439-96-5 |
| Nickel (Ni) | 0.01-1.5 | 7440-02-0 |
| Silicon (Si) | 1.0-3.5 | 7440-21-3 |
| Tin (Sn) | 0.1-0.15 | 7440-31-5 |

SECTION 6—FIRST AID MEASURES

EYE CONTACT: Not applicable

SKIN CONTACT: No special requirements

INGESTION:

Not applicable

INHALATION:

Not applicable

SECTION 5—FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES:

Not applicable

EXTINGUISHING MEDIA:

Not applicable

PROTECTION OF FIREFIGHTERS:

Not applicable

SECTION 6—ACCIDENTAL RELEASE MEASURES

Not applicable

SECTION 7—HANDLING & STORAGE

RECOMMENDED STORAGE

No special requirements

PROCEDURES FOR HANDLING

Proper hand and foot protection is recommended.

SECTION 8—EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING CONTROLS

None Required. There are no health hazards from castings in solid form.

| SUBSTANCE | ACGIH TLV mg/m ³ | OSHA PEL mg/m³ |
|-----------------|--------------------------------|-------------------|
| Carbon (C) | N/E | N/E |
| Chromium (Cr) | 0.5 | 1 |
| Copper (Cu) | 1 | 1 |
| Iron (Fe) | N/E | N/E |
| Manganese (Mn) | 0.02 (R); 0.1 (I) | 5 (C) |
| Nickel (Ni) | 1.5 (I) | 1 |
| Silicon (Si) | | |
| Total dust | N/E | 15 |
| Respirable dust | N/E | 5 |
| Tin (Sn) | 2 | 2 |

SUPPLEMENTAL INFORMATION

Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.

Furnes from hot processes may contain other compounds with different exposure limits than those listed above. Dust or furnes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Exposure limits for the most common contaminants are offered as reference. Please consult a competent person for guidance on exposure assessment and controls.

In particular, Hexavalent Chromium is an OSHA Expanded Health Standard; refer to OSHA 29 CFR 1910.1026-Chromium (VI) for complete requirements.

| SUBSTANCE | ACGIH TLV mg/m ³ | OSHA PEL |
|--|--------------------------------|------------|
| Chromium Compounds (as Cr) | mg/m | mg/m³ |
| Chromium (II) inorganic compounds | N/E | 0.5 |
| Chromium (III) inorganic compounds | 0.5 | 0.5 0.5 |
| Chromium (VI) inorganic compounds, certain water insoluble | 0.01 | 0.005 |
| Chromium (VI) inorganic compounds, water soluble | 0.05 | 0.005 |
| Chromium (VI) all forms and compounds | N/E | 0.005 |
| Copper Compounds (as Cu) | | 0.000 |
| Fume, as Cu | 0.2 | 0.1 |
| Dusts and mists, as Cu | 1 | 1 |
| Iron Compounds | | ' |
| Iron oxide (Fe ₂ O ₃) fume | N/E | 10 |
| Iron oxide (Fe ₂ O ₃) | 5 (R) | N/E |
| Nickel Compounds (as Ni) | | TAIL |
| Insoluble, inorganic compounds | 0.2(1) | 1 |
| Soluble, Inorganic compounds | 0.1(1) | |
| Nickel oxide | 0.2(1) | 1 |
| Γin compounds (as Sn) | | |
| Tin Oxide & inorganic compounds, except SnH ₄ | 2 | N/E |
| Inorganic compounds, except oxides, as Sn | N/E | 2 |
| Tin Oxides, as Sn | 2 | N/E |

TERMS

All exposure limits referenced above are 8 hour time weighted averages (TWA) unless otherwise noted.

None Established Ceiling Inhalable fraction

C=

1 =

R = Respirable fraction
TLV = Threshold Limit Value/American Conference of Industrial Hygienists (ACGIH)
PEL = Mg/m³ = mg/m³ = milligrams per cubic meter

PERSONAL PROTECTION:

Proper hand and foot protection is recommended.

SECTION 9—PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE /PHYSICAL STATE

| Solid, silver gray in color | |
|--|---|
| ODOR/ODOR THRESHOLD None | VAPOR DENSITY Not applicable |
| MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) | SPECIFIC GRAVITY (relative density) 7.85 g/cm³ for iron |
| BOILING POINT 5000°F (2750°C) for iron | VAPOR PRESSURE Not applicable |
| FLASH POINT Not applicable for solid castings | EVAPORATION RATE Not applicable |
| FLAMMABILITY Not flammable | SOLUBILITY IN WATER Insoluble |
| UPPER AND LOWER FLAMMABILITY LIMITS Not applicable for solid castings | pH Not applicable |
| AUTO IGNITION TEMPERATURE Not applicable | VISCOSITY Not applicable |

DECOMPOSITION TEMPERATURE

Not applicable

Not applicable

PARTITION COEFFICIENT

SECTION TO STREET STREET STREET

CHEMICAL STABILITY

是是是"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的"是一种"是一种"的

Stable

CONDITIONS TO AVOID

None

REACTIVITY INCOMPATIBLE MATERIALS

Not reactive None

HAZARDOUS DECOMPOSITION PRODUCTS

None

POSSIBILITY OF HAZARDOUS REACTIONS

Not applicable

SECTION 11 = (DX) GOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT:

None

SKIN:

None

INGESTION:

None None

Carcinogen Classification of Ingredients

| 1 | | | | |
|----------------|------|-----|------|--------------|
| INGREDIENT | OSHA | NTP | IARC | TARGET ORGAN |
| Nickel (metal) | NL | К | 2B | Lung, Nose |

TERMS

OSHA—Occupational Safety & Health Administration

Y = Listed as a Human Carcinogen

NTP—National Toxicology Program

K = Known to be a Human Carcinogen

R = Reasonably Anticipated to be a Human Carcinogen (RAHC)

IARC-International Agency for Research on Cancer

1 = Carcinogen to Humans

2A = Probably Carcinogenic to Humans

2B = Possibly Carcinogenic to Humans

3 = Unclassifiable as to Carcinogenicity in Humans

4 = Probably not Carcinogenic to Humans

Other

NL = Not Listed

| SECTION 12 | ECOLOGICAL INFORMATION |
|--|-------------------------------|
| ECOTOXICITY | PERSISTENCE AND DEGRADABILITY |
| Not applicable | Not applicable |
| BIOACCUMULATION POTENTIAL | MOBILITY IN SOIL |
| Not applicable | Not applicable |
| THE ADMINISTRATION OF THE PROPERTY OF THE PROP | |

OTHER ADVERSE EFFECTS

Not applicable

Gray Iron Castings

SECTION IS DISPOSAL CONSIDERATIONS

Recover or recycle if possible. Dispose of according to federal, state and local regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult federal, state and local regulations.

| SECTION 14-TRA | SPORT INFORMATION |
|--|--|
| And the second s | AND DESCRIPTION OF THE PARTY OF |

US DEPARTMENT OF TRANSPORTATION
(DOT)-HMR (Hazardous Materials Registration)
Not Regulated

UN SHIPPING NAME
Not regulated

CANADIAN TRANSPORTATION OF DANGEROUS
GOODS (TDG)
Not regulated

UN NUMBER
Not regulated

Page 4 of 6

| TRANSPORT HAZARD CLASS Not regulated | PACKING GROUP Not regulated |
|---------------------------------------|--|
| ENVIRONMENTAL HAZARDS None | LABEL(S) REQUIRED? No |
| TRANSPORT IN BULK Not applicable | SPECIAL SHIPPING INFORMATION Not applicable |

SECTION 15—REGULATORY INFORMATION

US-OSHA (Hazard Communication Standard)

Reference 29 CFR 1910.1200 and 1910.1000. A finished casting is an article as defined in the OSHA Hazard Communication Standard 29CFR 1910.1200 (c). Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as chromium, copper, iron, manganese, nickel, silicon, tin and silica.

For hexavalent chromium references see 29 CFR 1910.1026.

US-EPA (Toxic Substances Control Act-TSCA)

All components of these products are on the TSCA inventory list or are excluded from listing.

US-EPA (SARA Title III)

Releases to the environment of Chromium, Copper, Manganese and Nickel, may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 72.

CANADA-WHMIS (Workplace Hazardous Materials Information System)

This SDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and the SDS contains the information required by the CPR.

CANADA DSL (Domestic Substance List) Inventory Status

All components of these products are on the DSL Inventory.

CEPA (Canadian Environmental Protection Act)

Chromium and nickel are on the CEPA Priorities Substances Lists

EINECS No. (European Inventory of Existing Commercial Chemical Substances)

All components of these products are on the EINECS list.

RoHS (Restriction of Certain Hazardous Substances) Compliance

Castings comply with RoHS

CALIFORNIA PROPOSITION 65 Compliance

WARNING: This product contains or produces chemicals known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code 25248.5 et seq.)

US STATE REGULATORY INFORMATION

Some of the components listed in Section 3 may be covered under specific state regulations.

| OTHER INFORMATION |
|-------------------|
| DATE |
| 10/13 |
| 9,00 |
| |

NOTE:

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

Addendum: Label Information

PRODUCT IDENTIFIER

SC-000-041 Rev. 12

GRAY IRON CASTINGS

| SUPPLIER IDENTIFICATION | HAZARD PICTOGRAMS |
|--------------------------|-------------------|
| Company Name | None* |
| Street Address | |
| Mailing Address: | SIGNAL WORD |
| City State | None* |
| Zip/Postal Code Country | |
| Emergency Phone Number | |
| Other Info | 16 |
| | |
| PRECAUTIONARY STATEMENTS | HAZARD STATEMENTS |
| None* | None* |

*Castings do not present hazards in their original form.

OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Furnes from hot processes may contain other compounds with different exposure limits. Dust or furnes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 of the SDS for further information.