



SAFETY DATA SHEET

Issuing Date 20-Nov-2013

Revision Date 3-Jan-2017

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Lock-Ease Aerosol

Other means of identification

Product Code(s) LE-5, LE-5BK (765-1384)

UN-Number UN1950

Synonyms Lock Lubricant, Graphited Lock Fluid

Recommended use of the chemical and restrictions on use

Recommended Use All types of locks, household appliances, tools, guns, reels and other mechanisms.

Uses advised against No information available

Supplier's details

Supplier Address
AGS Company
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number 800-255-3924

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable aerosols	Category 1

GHS Label elements, including precautionary statements

Emergency Overview**Signal Word****Warning****Hazard Statements**

- Causes serious eye irritation
- May cause an allergic skin reaction
- May cause drowsiness or dizziness
-
- Extremely flammable aerosol
- Pressurized container: may burst if heated

**Appearance** Black, Liquid**Physical State** Aerosol.**Odor** Pungent**Precautionary Statements****Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Contaminated work clothing should not be allowed out of the workplace
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces - No smoking
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- None

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention
- Wash contaminated clothing before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Lock Lubricant, Graphited Lock Fluid

Chemical Name	CAS-No	Weight %	Trade secret
Alkanes, C7-8-iso-	70024-92-9	55-60	*
Acetone	67-64-1	15-20	*
Butane	106-97-8	10-15	*
Propane	74-98-6	5-10	*
Calcium Sulfonate	-	< 1	*

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

4. FIRST AID MEASURES**Description of necessary first-aid measures**

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists.
Skin Contact	Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Remove and wash contaminated clothing before re-use.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if exposed or you feel unwell.
Ingestion	Clean mouth with water and afterwards drink plenty of water.
Protection of First-aiders	Remove all sources of ignition. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Drowsiness. Dizziness. Central nervous system depression. Irritation.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Dry chemical. Foam. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Extremely flammable. Will form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal Precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Environmental Precautions**Environmental Precautions**

See Section 12 for additional Ecological Information

Methods and materials for containment and cleaning up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

For undamaged containers: Pick up and transfer to properly labeled containers. In case of rupture: Soak up with inert absorbent material. Take precautionary measures against static discharges. Use clean non-sparking tools to collect absorbed material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling**Handling**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not smoke. Do not puncture or incinerate cans. Contents under pressure. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities**Storage**

Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep at temperatures below 50° C.

Incompatible Products

Acids. Strong oxidizing agents. Oxygen.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³

Butane 106-97-8	TWA: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral	-
Benzene 71-43-2	STEL = 2.5 ppm TWA: 0.5 ppm S*	TWA: 1 ppm TWA: 10 ppm (vacated) TWA: 10 ppm (vacated) STEL: 50 ppm (vacated) Ceiling: 25 ppm Ceiling: 25 ppm STEL: 5 ppm	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls**Engineering Measures**

Eyewash stations. Showers. Explosion proof ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Tightly fitting safety goggles.

Skin and Body Protection

Wear protective gloves/clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Do not eat, drink or smoke when using this product. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Appearance	Black Liquid
Odor	Pungent	Odor Threshold	No information available
Property	Values	Remarks/ - Method	
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	No data available	None known	
Flash Point	No data available	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	12.8%		
lower flammability limit	1.0%		
Vapor Pressure	No data available	None known	
Vapor Density	Heavier than air	Air = 1	
Relative Density	No data available	None known	
Specific Gravity	0.69-0.75	For concentrate	
Water Solubility	Negligible	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition Temperature	No data available	None known	

Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Not flammable

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) 79%

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Temperatures above 50°C.

Incompatible materials

Acids. Strong oxidizing agents. Oxygen.

Hazardous decomposition products

Carbon oxides. Aldehydes. Nitrogen

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Product does not present an acute toxicity hazard based on known or supplied information. May cause irritation of respiratory tract. May cause drowsiness and dizziness. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye Contact

Causes serious eye irritation.

Skin Contact

May cause allergic skin reaction

Ingestion

Ingestion may cause irritation to mucous membranes. May cause additional affects as listed under "Inhalation".

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Butane	-	-	658 mg/L (Rat) 4 h
Propane	-	-	= 658 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Vapors may cause drowsiness and dizziness Irritation

Delayed and immediate effects and also chronic effects from short and long term exposure

Irritation Causes serious eye irritation
Sensitization Calcium sulfonate may cause skin sensitization.
Mutagenic Effects No information available.
Carcinogenicity Contains no ingredients above reportable quantities listed as a carcinogen.

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Reproductive Toxicity No information available.
STOT - single exposure May cause respiratory irritation
STOT - repeated exposure No information available.
Aspiration Hazard No information available.

Numerical measures of toxicity - Product

Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone 67-64-1		LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Benzene 71-43-2	EC50 72 h: = 29 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 10.7-14.7 mg/L flow-through (Pimephales promelas) LC50 96 h: 22330-41160 µg/L static (Pimephales promelas) LC50 96 h: 70000-142000 µg/L static (Lepomis macrochirus) LC50 96 h: = 22.49 mg/L static (Lepomis macrochirus) LC50 96 h: = 28.6 mg/L static (Poecilia reticulata) LC50 96 h: = 5.3 mg/L flow-through (Oncorhynchus mykiss)		EC50 48 h: 8.76 - 15.6 mg/L Static (Daphnia magna) EC50 48 h: = 10 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Acetone	-0.24
Butane	2.89
Propane	2.3

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging

Pressurized container: Do not pierce or burn, even after use. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number

D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream: F039		U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable

14. TRANSPORT INFORMATION**DOT**

UN-Number UN1950
Proper shipping name Aerosols, flammable
Hazard Class 2.1
Reportable Quantity (RQ) Acetone: RQ kg= 11350.00
Description UN1950, Aerosols, flammable, 2.1, RQ
Emergency Response Guide Number 126

TDG

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2
Description UN1950, Aerosols, 2.2

ICAO

UN-Number UN1950
Proper shipping name Aerosols
Hazard Class 2.2
Description UN1950, Aerosols, 2.2

IATA

UN-Number UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.2
ERG Code 10L
Description UN1950, Aerosols, flammable, 2.2

IMDG/IMO

UN-Number UN1950
Proper Shipping Name Aerosols

Hazard Class	2
Subsidiary Class	See SP63
EmS No.	F-D, S-U
Description	UN1950, Aerosols, 2.1 (See SP63)

UN-Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Description	UN1950, Aerosols, 2.1

ADR

UN-Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Tunnel Restriction Code	(D)
Description	UN1950, Aerosols, 2.1, (D)
ADR/RID-Labels	2.1

Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Benzene	71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X		X
Butane	X	X	X		X
Propane	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 3	Physical Hazard 1	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 20-Nov-2013
Revision Date 1-Jan-2017
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet