



We create chemistry

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 1/9
(30649611/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

ELASTOPOR®H 50490R RESIN

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals
Suitable for use in industrial sector: Polymers industry; chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: resin
Synonyms: Urethane System Resin Component

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit. 1 Serious eye damage/eye irritation

Label elements

Pictogram:

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 2/9
(30649611/SDS_GEN_US/EN)



Signal Word:
Danger

Hazard Statement:
H318 Causes serious eye damage.

Precautionary Statements (Prevention):
P280 Wear eye/face protection.

Precautionary Statements (Response):
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER, doctor/physician or emergency number 112.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

| <u>CAS Number</u> | <u>Weight %</u> | <u>Chemical name</u> |
|-------------------|-------------------|--|
| 67800-94-6 | >= 15.0 - < 20.0% | Benzenediamine, ar-methyl-, polymer with methyloxirane and oxirane |
| 15875-13-5 | >= 1.0 - < 3.0% | N,N',N''-tris(dimethylamino-propyl)-hexahydrotriazine |
| 280-57-9 | >= 1.0 - < 3.0% | triethylenediamine |

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:
Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 3/9
(30649611/SDS_GEN_US/EN)

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, carbon dioxide, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture.

Protection against fire and explosion:

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 4/9
(30649611/SDS_GEN_US/EN)

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Storage stability:

Storage temperature: 16 - 27 °C

Protect against moisture.

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

9. Physical and Chemical Properties

| | |
|--------------------|--------------------------------------|
| Form: | liquid |
| Odour: | amine-like |
| Odour threshold: | No applicable information available. |
| Colour: | brownish |
| pH value: | > 7.0 |
| : | 0.00 °C |
| Freezing point: | |
| Boiling point: | 100.00 °C (< 50.000000 mmHg) |
| | Unspecified |
| Sublimation point: | No applicable information available. |

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 6/9
(30649611/SDS_GEN_US/EN)

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral

Type of value: ATE

Value: 2,451 mg/kg

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

Irritation / corrosion

Assessment of irritating effects: May cause severe damage to the eyes. Skin contact causes slight irritation.

Sensitization

Assessment of sensitization: The chemical structure does not suggest a sensitizing effect. No applicable information available.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects. Repeated inhalative uptake of the substance did not cause substance-related effects. Repeated dermal uptake of the substance did not cause substance-related effects.

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 5/9
(30649611/SDS_GEN_US/EN)

| | | |
|---|--|--------------|
| Flash point: | > 94.00 °C | (closed cup) |
| Flammability: | not flammable | |
| Lower explosion limit: | For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point. | |
| Upper explosion limit: | For liquids not relevant for classification and labelling. | |
| Autoignition: | > 250 °C | |
| Vapour pressure: | < 1.00 mmHg (22.80 °C) | |
| Density: | 1.0870 g/cm ³ (20.00 °C) | |
| Relative density: | No applicable information available. | |
| Vapour density: | No applicable information available. | |
| Partitioning coefficient n-octanol/water (log Pow): | not applicable | |
| Self-ignition temperature: | not self-igniting | |
| Thermal decomposition: | No decomposition if stored and handled as prescribed/indicated. | |
| Viscosity, dynamic: | 2,442.000 mPa.s (22.80 °C) | |
| Viscosity, kinematic: | No applicable information available. | |
| Solubility in water: | slightly soluble | |
| Solubility (quantitative): | No applicable information available. | |
| Solubility (qualitative): | No applicable information available. | |
| Evaporation rate: | Value can be approximated from Henry's Law Constant or vapor pressure. | |
| Other Information: | If necessary, information on other physical and chemical parameters is indicated in this section. | |

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Not an oxidizer.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Incompatible materials

acids, oxidizing agents, isocyanates

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 7/9
(30649611/SDS_GEN_US/EN)

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Medical conditions aggravated by overexposure

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Mobility in soil

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 8/9
(30649611/SDS_GEN_US/EN)

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK

PA

CAS Number

25265-71-8

Chemical name

dipropylene glycol

Safety Data Sheet

ELASTOPOR®H 50490R RESIN

Revision date : 2018/08/02
Version: 5.0

Page: 9/9
(30649611/SDS_GEN_US/EN)

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 1 Special:

HMIS III rating

Health: 3 Flammability: 1 Physical hazard: 1

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2018/08/02

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ELASTOPOR is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. BASF CORPORATION WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.

END OF DATA SHEET

