

# SAFETY DATA SHEET



## Section 1. Identification

Product name BP Unleaded Gasolines  
 SDS # 12631  
 Code 12631

### Relevant identified uses of the substance or mixture and uses advised against

Product use USE AS MOTOR FUEL ONLY.

Supplier BP Products North America Inc.  
 150 West Warrenville Road  
 Naperville, Illinois 60563-8460  
 USA

EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735  
 Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT INFORMATION 1 (866) 4 BP - MSDS  
 (866-427-6737 Toll Free - North America)  
 email: bpcares@bp.com

## Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture  
 FLAMMABLE LIQUIDS - Category 1  
 SKIN IRRITATION - Category 2  
 EYE IRRITATION - Category 2A  
 GERM CELL MUTAGENICITY - Category 1B  
 CARCINOGENICITY - Category 1A  
 TOXIC TO REPRODUCTION (Unborn child) - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
 ASPIRATION HAZARD - Category 1

### GHS label elements

#### Hazard pictograms



#### Signal word

Danger

#### Hazard statements

Extremely flammable liquid and vapor.  
 Causes serious eye irritation.  
 Causes skin irritation.  
 May cause genetic defects.  
 May cause cancer.  
 Suspected of damaging the unborn child.  
 May be fatal if swallowed and enters airways.  
 May cause drowsiness and dizziness.

### Precautionary statements

Product name	BP Unleaded Gasolines	Product code	12631	Page:	1/21
Version	1	Date of issue	12/16/2014.	Format	US
			(US)	Language	ENGLISH
					(ENGLISH)

## Section 2. Hazards identification

Prevention	Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Avoid breathing vapor. Wash thoroughly after handling. Avoid release to the environment.
Response	IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Store in well-ventilated place. Keep container tightly closed.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	Contains Benzene. Prolonged or repeated exposure to benzene can cause anaemia and other blood diseases, including leukemia. See toxicological information (Section 11).

## Section 3. Composition/information on ingredients

Substance/mixture	Mixture	
Ingredient name	CAS number	%
Gasoline	Mixture	90 - 100
Ethanol	64-17-5	0 - 10
Contains:		
Benzene	71-43-2	0 - 3
Cyclohexane	110-82-7	0 - 1
Ethylbenzene	100-41-4	0 - 2
Toluene	108-88-3	4 - 11
1,2,4-Trimethylbenzene	95-63-6	0 - 3
xylene	1330-20-7	4 - 11
Naphthalene	91-20-3	0 - 0.5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention.  If exposure to vapor, mists or fumes causes drowsiness, headache, blurred vision or irritation of the eyes, nose or throat, remove immediately to fresh air. Keep patient warm and at rest. If any symptoms persist obtain medical advice.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical attention immediately.

## Section 4. First aid measures

**Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treatment should in general be symptomatic and directed to relieving any effects. Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal intubation. Monitor for cardiac dysrhythmias.

**Specific treatments** No specific treatment.

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray. This substance will float and can be reignited on surface water.

**Unsuitable extinguishing media** Do not use water jet. Never use water.

**Specific hazards arising from the chemical** Flammable liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

**Hazardous combustion products** Combustion products may include the following:  
carbon dioxide  
carbon monoxide  
other hazardous substances.

**Special protective actions for fire-fighters** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

**Special remarks on fire hazards** Do not use water jet.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Eliminate all ignition sources. Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained positive pressure breathing apparatus (SCBA).

## Section 6. Accidental release measures

For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
Environmental precautions	Liquid leaks generate large volumes of flammable vapor, heavier than air, which may travel to remote sources of ignition (eg. along drainage systems). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill	Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.
Large spill	Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Dike spill area and do not allow product to reach sewage system and surface or ground water. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid exposure during pregnancy. Do not swallow. Aspiration hazard if swallowed. Can enter lungs and cause damage. Never siphon by mouth.
Advice on general occupational hygiene	To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.  Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Product name BP Unleaded Gasolines

Product code 12631

Page: 4/21

Version 1 Date of issue 12/16/2014.

Format US

Language ENGLISH

(US)

(ENGLISH)

## Section 7. Handling and storage

Light hydrocarbon vapors can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapor in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks. Do not enter storage tanks. If entry to vessels is necessary, follow permit to work procedures. Entry to any tanks or other confined space requires a full risk assessment and appropriate control measures to be put in place in conformance with appropriate regulations and industry practice on confined space entry. When the product is pumped (e.g. during filling, discharge or ullaging) and when sampling, there is a risk of static discharge. Ensure equipment used is properly earthed or bonded to the tank structure. Electrical equipment should not be used unless it is intrinsically safe (i.e. will not produce sparks). Explosive air/vapor mixtures may form at ambient temperature. If product comes into contact with hot surfaces, or leaks occur from pressurized fuel pipes, the vapor or mists generated will create a flammability or explosion hazard. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Do not enter storage tanks without breathing apparatus unless the tank has been well ventilated and the tank atmosphere has been shown to contain hydrocarbon vapor concentrations of less than 1% of the lower flammability limit and an oxygen concentration of at least 20% volume.

Light hydrocarbon vapors can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapor in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks. When the product is pumped (e.g. during filling, discharge or ullaging) and when sampling, there is a risk of static discharge. Ensure equipment used is properly earthed or bonded to the tank structure. Electrical equipment should not be used unless it is intrinsically safe (i.e. will not produce sparks).

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Gasoline	<b>ACGIH TLV (United States).</b> TWA: 300 ppm 8 hours. Issued/Revised: 5/1996 TWA: 890 mg/m <sup>3</sup> 8 hours. Issued/Revised: 5/1996 STEL: 500 ppm 15 minutes. Issued/Revised: 5/1996 STEL: 1480 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 5/1996
Ethanol	<b>ACGIH TLV (United States).</b> STEL: 1000 ppm 15 minutes. Issued/Revised: 11/2008 <b>OSHA PEL (United States).</b> TWA: 1900 mg/m <sup>3</sup> 8 hours. Issued/Revised: 6/1993 TWA: 1000 ppm 8 hours. Issued/Revised: 6/1993
Benzene	<b>ACGIH TLV (United States). Absorbed through skin.</b> STEL: 8 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 5/1997 STEL: 2.5 ppm 15 minutes. Issued/Revised:



## Section 8. Exposure controls/personal protection

xylene	<p>5/1997 TWA: 1.6 mg/m<sup>3</sup> 8 hours. Issued/Revised: 5/1997 TWA: 0.5 ppm 8 hours. Issued/Revised: 5/1997 <b>OSHA PEL (United States).</b> STEL: 5 ppm 15 minutes. Issued/Revised: 6/1993 TWA: 1 ppm 8 hours. Issued/Revised: 6/1993 <b>OSHA PEL Z2 (United States).</b> AMP: 50 ppm 10 minutes. Issued/Revised: 6/1993 CEIL: 25 ppm Issued/Revised: 6/1993 TWA: 10 ppm 8 hours. Issued/Revised: 6/1993</p> <p><b>ACGIH TLV (United States).</b> STEL: 651 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 5/1996 STEL: 150 ppm 15 minutes. Issued/Revised: 5/1996 TWA: 434 mg/m<sup>3</sup> 8 hours. Issued/Revised: 5/1996 TWA: 100 ppm 8 hours. Issued/Revised: 5/1996 <b>OSHA PEL (United States).</b> TWA: 435 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 TWA: 100 ppm 8 hours. Issued/Revised: 6/1993</p>
toluene	<p><b>OSHA PEL Z2 (United States).</b> AMP: 500 ppm 10 minutes. Issued/Revised: 6/1993 CEIL: 300 ppm Issued/Revised: 6/1993 TWA: 200 ppm 8 hours. Issued/Revised: 6/1993 <b>ACGIH TLV (United States).</b> TWA: 20 ppm 8 hours. Issued/Revised: 11/2006</p>
1,2,4-Trimethylbenzene	<p><b>ACGIH TLV (United States).</b> TWA: 123 mg/m<sup>3</sup> 8 hours. Issued/Revised: 9/1994 TWA: 25 ppm 8 hours. Issued/Revised: 9/1994</p>
ethylbenzene	<p><b>ACGIH TLV (United States).</b> TWA: 20 ppm 8 hours. Issued/Revised: 12/2010 <b>OSHA PEL (United States).</b> TWA: 435 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 TWA: 100 ppm 8 hours. Issued/Revised: 6/1993</p>
cyclohexane	<p><b>ACGIH TLV (United States).</b> TWA: 100 ppm 8 hours. Issued/Revised: 1/2002 <b>OSHA PEL (United States).</b> TWA: 1050 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 TWA: 300 ppm 8 hours. Issued/Revised: 6/1993</p>
naphthalene	<p><b>ACGIH TLV (United States). Absorbed</b></p>

## Section 8. Exposure controls/personal protection

through skin.

TWA: 52 mg/m<sup>3</sup> 8 hours. Issued/Revised:  
5/1996

TWA: 10 ppm 8 hours. Issued/Revised:  
5/1996

**OSHA PEL (United States).**

TWA: 50 mg/m<sup>3</sup> 8 hours. Issued/Revised:  
6/1993

TWA: 10 ppm 8 hours. Issued/Revised:  
6/1993

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

Chemical splash goggles.

#### Skin protection

##### Hand protection

Wear chemical resistant gloves. Gloves made from fluoroelastomer resistant to hydrocarbons and a wide range of chemicals. Nitrile gloves.

Do not re-use gloves. Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture). Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.

Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

##### Body protection

Use of protective clothing is good industrial practice. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Wear suitable protective clothing. Footwear highly resistant to chemicals. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For greatest effectiveness against static electricity, overalls, boots and gloves should all be anti-static. When there is a risk of ignition wear inherently fire resistant protective clothes and gloves. Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal

## Section 8. Exposure controls/personal protection

clothes. When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapor or mist. If ventilation is inadequate, use a NIOSH certified respirator with an organic vapor cartridge and P95 particulate filter.

If operating conditions cause high vapor concentrations or the TLV is exceeded, use NIOSH-certified, supplied-air respirator.

Use with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

### Appearance

Physical state	Liquid.
Color	Clear
Odor	Hydrocarbon.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point	26.67 to 221°C (80 to 430°F)
Flash point	Closed cup: -42.778°C (-45°F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Lower: 1.3% Upper: 7.6% (Estimated.)
Vapor pressure	48.134 to 103.146 kPa (361.97 to 775.66 mm Hg)
Vapor density	3 to 4 [Air = 1]
Density	750 kg/m <sup>3</sup> (0.75 g/cm <sup>3</sup> )
Solubility	Very slightly soluble in water
Solubility	Very slightly soluble in the following materials: cold water.
Partition coefficient: n-octanol/water	>3
Auto-ignition temperature	257°C (494.6°F)
Decomposition temperature	Not available.
Viscosity	Not available.

Product name BP Unleaded Gasolines

Product code 12631

Page: 8/21

Version 1 Date of issue 12/16/2014.

Format US

Language ENGLISH

(US)

(ENGLISH)



## Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Keep away from heat, sparks and flame. Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials. Chlorine and Fluorine
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Species	Result	Exposure	Remarks
Gasoline	LC50 Inhalation Vapor	Rat	>5610 g/m <sup>3</sup> analytical	4 hours	Based on Gasoline
	LC50 Inhalation Vapor	Rat	>7630 mg/m <sup>3</sup> Nominal	4 hours	Based on Gasoline
	LD50 Dermal	Rabbit	>2000 mg/kg	-	Based on Gasoline
	LD50 Oral	Rat	>5000 mg/kg	-	Based on Gasoline
Ethanol	LC50 Inhalation Vapor	Rat	124.7 mg/l	4 hours	Based on Ethanol
	LC50 Inhalation Vapor	Rat	116.9 mg/l	4 hours	Based on Ethanol
	LC50 Inhalation Vapor	Rat	133.8 mg/l	4 hours	Based on Ethanol
	LD50 Oral	Rat	10470 mg/kg	-	Based on Ethanol

Conclusion/Summary Not available.

#### Irritation/Corrosion

Product/ingredient name	Species	Result	Score	Exposure	Observation	Conc.	Remarks
Gasoline	Rabbit	Skin - Irritant	-	-	-	-	Based on Gasoline
	Rabbit	Eyes - Non-irritating to the eyes.	-	-	-	-	Based on Gasoline
Ethanol	Rabbit	Skin - Non-irritant to skin.	-	-	-	-	Based on Ethanol

## Section 11. Toxicological information

Rabbit	Eyes - Cornea opacity	-	-	-	-	Based on Ethanol
Rabbit	Eyes - Iris lesion	-	-	-	-	Based on Ethanol
Rabbit	Eyes - Irritant	-	-	-	-	Based on Ethanol

### Sensitizer

Product/ingredient name	Route of exposure	Species	Result	Remarks
Gasoline	skin	Guinea pig	Not sensitizing	Based on Gasoline

### Mutagenicity

Product/ingredient name	Test	Experiment	Result	Remarks
Gasoline	Equivalent to OECD 476	Experiment: In vitro Subject: Mammal - species unspecified	Negative	Based on Gasoline
	Equivalent to OECD 471	Experiment: In vitro Subject: Non-mammalian species	Negative	Based on Gasoline
	EPA OPPTS 870.5395	Experiment: In vivo Subject: Unspecified Cell: Germ	Negative	Based on Gasoline vapor condensate
	Equivalent to OECD 475	Experiment: In vivo Subject: Unspecified Cell: Germ	Negative	Based on Gasoline
Ethanol	Equivalent to OECD 476	Experiment: In vitro Subject: Mammal - species unspecified	Negative	Based on Ethanol
	Equivalent to OECD 473	Experiment: In vitro Subject: Non-mammalian species	Negative	Based on Ethanol
	Equivalent to OECD 478	Experiment: In vivo Subject: Unspecified Cell: Germ	Negative	Based on Ethanol

Conclusion/Summary May cause genetic defects.

### Carcinogenicity

Product/ingredient name	Test	Species	Experiment	Duration	Result	Remarks
Gasoline	Equivalent to OECD 451	Rat	Inhalation	113 weeks	Negative - Inhalation - Unspecified	Based on Gasoline
	Equivalent to OECD 451	Mouse	Dermal	102 weeks	Negative - Dermal - Unspecified	Based on Gasoline
Ethanol	EPA OPPTS 870.4200	Mouse	Oral	105 weeks	Positive - Oral - Unspecified	Based on Ethanol

## Section 11. Toxicological information

Equivalent - Rat Oral 104 weeks Negative - Based on  
to OECD Oral - Ethanol  
Unspecified

Conclusion/Summary May cause cancer

### Classification

Product/ingredient name	OSHA	IARC	NTP
Gasoline	-	2B	-
toluene	-	3	-
xylene	-	3	-
Benzene	+	1	Known to be a human carcinogen.
ethylbenzene	-	2B	-
naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.

IARC :

1 - Carcinogenic to human.

2B - Possible carcinogen to human.

3 - Not classifiable as a human carcinogen.

NTP :

Proven - Known to be human carcinogens.

Possible - Reasonably anticipated to be human carcinogens.

OSHA :

+ Potential occupational carcinogen

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Result	Exposure
Gasoline	-	Negative	-	Rat	Inhalation	2 generation
	-	-	Negative	Rat	Inhalation	14 days
Ethanol	-	Positive	-	Rat	Oral	2 generation
	-	-	Negative	Rat	Inhalation	18 days

Conclusion/Summary

Development: Suspected of damaging the unborn child.

Fertility: Not classified. Based on available data, the classification criteria are not met.

Effects on or via lactation: Not classified. Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Gasoline	Category 3	Not applicable.	Narcotic effects
xylene	Category 3	Not applicable.	Respiratory tract irritation
toluene	Category 3	Not applicable.	Narcotic effects
1,2,4-Trimethylbenzene	Category 3	Not applicable.	Respiratory tract irritation
ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation
cyclohexane	Category 3	Not applicable.	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 2	Not determined	ears
Benzene	Category 1	Not determined	blood system

### Aspiration hazard

Product name BP Unleaded Gasolines

Product code 12631

Page: 11/21

Version 1 Date of issue 12/16/2014.

Format US

Language ENGLISH

(US)

(ENGLISH)

## Section 11. Toxicological information

Name	Result
Gasoline	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1
Benzene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
cyclohexane	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation.
Inhalation	Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Ingestion	Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach. Aspiration hazard if swallowed – harmful or fatal if liquid is aspirated into lungs.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Skin contact	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Inhalation	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Ingestion	Adverse symptoms may include the following: nausea or vomiting reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

#### Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

#### Potential chronic health effects

General	Solvent "sniffing" (abuse) or intentional overexposure to vapors can produce serious central nervous system effects, including unconsciousness, and possibly death.
Carcinogenicity	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	May cause genetic defects.
Teratogenicity	Suspected of damaging the unborn child.
Developmental effects	No known significant effects or critical hazards.

Product name	BP Unleaded Gasolines	Product code	12631	Page: 12/21
Version 1	Date of issue 12/16/2014.	Format	US (US)	Language ENGLISH (ENGLISH)

## Section 11. Toxicological information

### Fertility effects

No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

### Other information

Aspiration of this product into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Do not siphon by mouth.

### Additional information

Gasoline - Excess exposure to vapors may produce headaches, dizziness, nausea, drowsiness, irritation of eyes, nose and throat and central nervous system depression. Aspiration of this material into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Inhalation of unleaded gasoline vapors did not produce birth defects in laboratory animals. Ingestion of this material can cause gastrointestinal irritation and diarrhea.

In a long-term inhalation study of whole unleaded gasoline vapors, exposure-related kidney damage and kidney tumors were observed in male rats. Similar kidney effects were not seen in female rats or in mice. At the highest exposure level (2056 ppm), female mice had an increased incidence of liver tumors. Results from subsequent scientific studies have shown that a broad variety of chemicals cause these kidney effects only in the male rat. Further studies have discovered the means by which the physiology of the male rat uniquely predispose it to these effects. Consequently, the Risk Assessment Forum of the Environmental Protection Agency has recognized that these responses are not predictive of a human health hazard. The liver tumors that were increased in the high-dose female mice are likewise of questionable significance because of their high spontaneous occurrence even without chemical exposure and because the rate of their occurrence is accelerated by a broad spectrum of chemicals not commonly considered to be carcinogens (e.g., phenobarbital). Thus, the significance of the mouse liver tumor response in terms of human health is questionable.

Gasoline is a complex mixture of hydrocarbons and contains benzene (typically no more than 2 volume%), toluene, and xylene. Chronic exposure to high levels of benzene has been shown to cause cancer (leukemia) in humans and other adverse blood effects (anemia). Benzene is considered a human carcinogen by IARC, NTP and OSHA. Over exposure to xylene and toluene can cause irritation to the upper respiratory tract, headache and narcosis. Some liver damage and lung inflammation were seen in chronic studies on xylene in guinea pigs but not in rats.

Solvent "sniffing" (abuse) or intentional overexposure to vapors can produce serious central nervous system effects, including unconsciousness, and possibly death.

Gasoline as a mixture is classified as a 2B (possible human) carcinogen by IARC.

Gasoline engine exhaust is classified as possibly carcinogenic to humans by IARC (2B). This classification is based primarily on animal and in vitro studies of gasoline engine exhaust condensates/extracts. Studies of the gaseous exhaust stream in animals did not provide sufficient evidence for classification as a carcinogen.

Gasoline: Additional toxicity information on the components:

Benzene: Acute toxicity of benzene results primarily from depression of the central nervous system (CNS). Inhalation of concentrations over 50 ppm can produce headache, lassitude, weariness, dizziness, drowsiness, or excitation. Exposure to very high levels can result in unconsciousness and death.



## Section 11. Toxicological information

**Benzene:** Long-term overexposure to benzene has been associated with certain types of leukemia in humans. In addition, the International Agency for Research on Cancer (IARC), the National Toxicology Program, and OSHA consider benzene to be a human carcinogen. Chronic exposures to high levels of benzene have been reported to cause adverse blood effects including anemia. Benzene exposure can occur by inhalation and absorption through the skin.

Inhalation and forced feeding studies of benzene in laboratory animals have produced a carcinogenic response in a variety of organs, including possibly leukemia, other adverse effects on the blood, chromosomal changes and some effects on the immune system. Exposure to benzene at levels up to 300 ppm did not produce birth defects in animal studies; however, exposure to higher dosage levels resulted in a reduction of body weight of the rat pups (fetotoxicity). Changes in the testes have been observed in mice exposed to benzene at 300 ppm, but reproductive performance was not altered in rats exposed to benzene at the same level. Aspiration of this material into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this material.

**Toluene:** Aspiration of this material into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this material. Deliberate inhalation of high concentrations of toluene has been linked to damage of the brain, liver and kidney. Inhalation of very high concentrations of toluene, such as in cases of solvent abuse, has resulted in sudden death which may be a result of cardiac arrhythmia or central nervous system depression. Mental and/or growth retardation has been reported in children of women who deliberately inhale toluene during pregnancy (usually at thousands of ppm). Fetal developmental toxicity was observed when pregnant rats were exposed to toluene at levels of 1500 ppm. Maternal toxicity was also observed at this concentration. Prolonged, high level exposure to toluene in laboratory animals has resulted in hearing loss. Exposure studies in rats have resulted in adverse effects on the kidney, liver and central nervous system. Studies in occupationally exposed individuals indicate that toluene exposure has been associated with impaired color vision and decreased performance in some neurobehavioral tests. There are occupational studies which report an association between inhalation exposure to toluene and adverse effects on reproduction including spontaneous abortion. The methodology of these studies and the reliability of the results have been questioned. In a two-generation study in rats, inhalation of toluene at levels up to 2000 ppm did not produce adverse effects on fertility or reproductive performance.

**Xylenes:** Xylene has been reported to cause central nervous system effects at concentrations above the recommended exposure limit. Xylene vapor becomes irritating at relatively high levels. In one study, eye irritation was reported at exposures of 460 ppm and in one person at 230 ppm after 15 minutes. In another study, no one reported eyes, nose and throat irritation at mixed xylene exposures up to 230 ppm for 30 minutes. Dermal LD50 is expected to be greater than 10g/kg in rabbits, based on test results from similar materials.

Mixed xylenes caused slight hearing loss in rats exposed to 800 ppm in the air for 14 hours/day for six weeks. There is no information available for lower concentrations; however, similar chemicals that have caused these hearing effects at similar concentrations have not caused effects at lower concentrations.

Pregnant animals exposed to xylene or its isomers have been reported to cause development toxicity in rodents when exposed by inhalation. The developmental effects observed consisted of delayed development and minor skeletal variations, but no malformations. Because of the high exposure levels used in these studies, we do not believe that these results imply an increased risk of reproductive toxicity to workers exposed to xylene levels at or below the exposure limits.

Xylene and its isomers are not genotoxic.

Technical grade xylene has been tested in a National Toxicology Program carcinogenicity study in rats and mice dosed orally for two years. There was no evidence of carcinogenicity.

**Ethylbenzene:** The National Toxicology Program (NTP) conducted a 13-week inhalation study with male and female rats and mice at exposure concentrations ranging from 100

Product name	BP Unleaded Gasolines	Product code	12631	Page:	14/21
Version	1	Date of issue	12/16/2014.	Format	US
				(US)	(US)
				Language	ENGLISH
					(ENGLISH)

## Section 11. Toxicological information

to 1000 ppm ethylbenzene. No rats or mice died during the study. Kidney, liver, and lung weights were increased in the exposed rats, while weight increases were observed only in the livers of exposed mice. Treatment-related histopathologic changes were not observed in any tissues of rats and mice.

NTP also exposed male and female rats and mice by inhalation to 0, 75, 250, or 750 ppm ethylbenzene for 2 years. There was a statistically significant increase in the number of kidney tumors in male and female rats at 750 ppm. There were also increased incidences of lung tumors in male mice and liver tumors in female mice that were statistically significant at 750 ppm. Except for the male rat kidney tumors, the incidence of the tumors were within the range observed for non-exposed animals from other studies conducted by NTP. The significance of these findings to humans is unknown. Ethylbenzene is not genotoxic. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and found it to be possibly carcinogenic to humans (Group 2B).

Ethylbenzene is not genotoxic.

This product contains trimethylbenzenes. These compounds cause irritation to the eyes, nose and respiratory tract. Repeated dermal exposure can defat and irritate the skin. Inhalation may cause dizziness and drowsiness. Studies in laboratory animals with mixtures of C9 aromatic hydrocarbons produced adverse effects on development such as increased fetal mortality, reduced fetal weight, and delayed ossification at high exposure concentrations. Effects were reduced if exposure was terminated prior to delivery. There was no evidence of reproductive toxicity.

Naphthalene has been reported to cause developmental toxicity in mice after oral exposure to relatively high dose levels, but developmental toxicity was not observed in NTP (National Toxicology Program) sponsored studies in rats and rabbits. Ingestion or inhalation of naphthalene can result in hemolysis and other blood abnormalities, and individuals (and infants) deficient in glucose-6-phosphate dehydrogenase may be especially susceptible to these effects. Inhalation of naphthalene may cause headache and nausea. Airborne exposure can result in eye irritation. Naphthalene exposure has been associated with cataracts in animals and humans.

Ethanol - Human data: In humans excessive consumption of alcoholic beverages during pregnancy is associated with the induction of Fetal Alcohol Syndrome in the offspring. Reduced birth weight and physical and mental defects occur. There is no evidence that such effects might be caused by exposures other than direct ingestion of alcoholic drinks. In humans high lifetime consumption of alcoholic beverages can be associated with certain cancers and effects on the liver. There is no evidence that these can be caused by exposure other than direct ingestion of alcoholic drinks (IARC 1988).

## Section 12. Ecological information

### Toxicity

No testing has been performed by the manufacturer.

Product/ingredient name	Species	Test/Result	Exposure	Effects	Remarks
Gasoline	Micro-organism	Acute EC50 15.41 mg/l Nominal Fresh water	40 hours	growth inhibition	-
	Algae	Acute EL50 3.1 mg/l Nominal Fresh water	72 hours	(growth rate)	Based on Gasoline
	Algae	Acute EL50 3.7 mg/l Nominal Fresh water	96 hours	(growth rate)	Based on Gasoline
	Daphnia	Acute EL50 4.5 mg/l Nominal Fresh water	48 hours	Mobility	Based on straight-run light gasoline
	Fish	Acute LL50 10 mg/l Nominal	96 hours	Mortality	Based on Naphtha

Product name BP Unleaded Gasolines

Product code 12631

Page: 15/21

Version 1 Date of issue 12/16/2014.

Format US  
(US)

Language ENGLISH  
(ENGLISH)

## Section 12. Ecological information

		Fresh water			(petroleum), isomerisation
	Fish	Acute LL50 8.2 mg/l Nominal Fresh water	96 hours	Mortality	Based on Naphtha (petroleum), light alkylate
	Algae	Acute NOELR 0. 5 mg/l Nominal Fresh water	72 hours	(growth rate)	Based on Gasoline
	Daphnia	Acute NOELR 0. 5 mg/l Nominal Fresh water	48 hours	Mobility	Based on Straight run gas oil
	Daphnia	Chronic EL50 10 mg/l Nominal Fresh water	21 days	Reproduction	Based on Naphtha (petroleum), light alkylate
	Daphnia	Chronic EL50 >40 mg/l Nominal Fresh water	21 days	Mobility	Based on Naphtha (petroleum), light alkylate
	Fish	Chronic EL50 10 mg/l Nominal Fresh water	21 days	Reproduction	Based on: Naphtha (petroleum), light alkylate; read across between species
	Fish	Chronic LL50 5.2 mg/l Nominal Fresh water	14 days	Mortality	Based on Naphtha (petroleum), light catalytic reformed
	Daphnia	Chronic NOELR 2.6 mg/l Nominal Fresh water	21 days	Reproduction	Based on Naphtha (petroleum), light alkylate
	Daphnia	Chronic NOELR 16 mg/l Nominal Fresh water	21 days	Mobility	Based on Naphtha (petroleum), light alkylate
	Fish	Chronic NOELR 2.6 mg/l Nominal Fresh water	14 days	Mortality	Based on Naphtha (petroleum), light catalytic reformed
	Fish	Chronic NOELR 2.6 mg/l Nominal Fresh water	21 days	Reproduction	Based on: Naphtha (petroleum), light alkylate; read across between species
	soil, plants	Chronic PNEC >0. - 4 mg/kg	-	-	-
Ethanol	Algae	EC50 675 mg/l	4 days	-	Based on Ethanol
	Aquatic plants	EC50 4432 mg/l	7 days	-	Based on Ethanol

Product name BP Unleaded Gasolines

Product code 12631

Page: 16/21

Version 1 Date of issue 12/16/2014.

Format US

Language ENGLISH

(US)

(ENGLISH)

## Section 12. Ecological information

Daphnia	Acute LC50 5012 mg/l	48 hours	-	Based on Ethanol
Fish	Acute LC50 153 g/l	96 hours	-	Based on Ethanol
Fish	Acute LC50 14.2 g/l	96 hours	-	Based on Ethanol
Daphnia	Chronic LC50 2 mg/l	10 days	-	Based on Ethanol
Daphnia	Chronic LC50 9.6 mg/l	9 days	-	Based on Ethanol

**Conclusion/Summary** Not available.

### Persistence and degradability

Partially biodegradable.

Product/ingredient name	Test	Result	Remarks
Ethanol	EPA	95 % - Readily - 15 days	Based on Ethanol
	EPA	84 % - Readily - 20 days	Based on Ethanol
	EPA	74 % - Readily - 5 days	Based on Ethanol
	EPA	74 % - Readily - 10 days	Based on Ethanol

**Conclusion/Summary** Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Ethanol	-	-	Readily

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** Not available.

**Mobility** Spillages may penetrate the soil causing ground water contamination.

**Other ecological information** Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

**Disposal methods** The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.






**United States - RCRA Toxic hazardous waste "U" List**

Product name	BP Unleaded Gasolines	Product code	12631	Page:	17/21
Version	1	Date of issue	12/16/2014.	Format	US
			(US)	Language	ENGLISH
					(ENGLISH)

## Section 13. Disposal considerations

Ingredient	CAS #	Status	Reference number
Xylene	1330-20-7	Listed	U239
Toluene; Benzene, methyl-	108-88-3	Listed	U220
Benzene (I,T)	71-43-2	Listed	U019
Cyclohexane (I); Benzene, hexahydro- (I)	110-82-7	Listed	U056

## Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN1203	UN1203	UN1203	UN1203
UN proper shipping name	GASOLINE	GASOLINE	MOTOR SPIRIT or GASOLINE or PETROL MARINE POLLUTANT	Motor spirit or Gasoline or Petrol
Transport hazard class(es)	3 	3 	3  	3 
Packing group	II	II	II	----
Environmental hazards	No.	No.	Yes.	No.
Additional information	<u>Reportable quantity</u> 333.33 lbs / 151.33 kg [53.304 gal / 201.78 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. <u>Limited quantity</u> Yes. <u>Packaging instruction</u> Passenger aircraft Quantity	The marine pollutant mark is not required when transported by road or rail. <u>Explosive Limit and Limited Quantity Index</u> 30 <u>Passenger Carrying Ship Index</u> 100 <u>Passenger Carrying Road or Rail Index</u> 5 <u>Special provisions</u> 17, 82, 88	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency schedules (EmS)</u> F-E, S-E <u>Special provisions</u> 243	The environmentally hazardous substance mark may appear if required by other transportation regulations. <u>Passenger and Cargo Aircraft</u> Quantity limitation: 5 L Packaging instructions: 353 <u>Cargo Aircraft</u> <u>Only</u> Quantity limitation: 60 L Packaging instructions: 364 <u>Limited Quantities - Passenger Aircraft</u>



## Section 14. Transport information

	limitation: 5 L			Quantity limitation: 1 L
	Cargo aircraft Quantity limitation: 60 L			Packaging instructions: Y341
	<u>Special provisions</u> 144, 177, B1, B33, IB2, T4, TP1			<u>Special provisions</u> A100

Special precautions for user Not available.

Transport in bulk according  
to Annex II of MARPOL  
73/78 and the IBC Code

Proper shipping name

MARPOL Annex 1 rules apply for bulk shipments by  
sea.  
Category: gasoline and spirits

## Section 15. Regulatory information

### U.S. Federal regulations

United States inventory  
(TSCA 8b)

All components are listed or exempted.

### SARA 302/304

#### Composition/information on ingredients

No products were found.

### SARA 311/312

Classification

Fire hazard  
Immediate (acute) health hazard  
Delayed (chronic) health hazard

### SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	toluene	108-88-3	4 - 11
	xylene	1330-20-7	4 - 11
	Benzene	71-43-2	0 - 3
	1,2,4-Trimethylbenzene	95-63-6	0 - 3
	ethylbenzene	100-41-4	0 - 2
	cyclohexane	110-82-7	0 - 1
	naphthalene	91-20-3	0 - 0.5
Supplier notification	toluene	108-88-3	4 - 11
	xylene	1330-20-7	4 - 11
	Benzene	71-43-2	0 - 3
	1,2,4-Trimethylbenzene	95-63-6	0 - 3
	ethylbenzene	100-41-4	0 - 2
	cyclohexane	110-82-7	0 - 1
	naphthalene	91-20-3	0 - 0.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

Massachusetts

The following components are listed: XYLENE; TOLUENE; ETHYL ALCOHOL;  
BENZENE; PSEUDOCUMENE; ETHYL BENZENE; CYCLOHEXANE

New Jersey

The following components are listed: XYLENES; BENZENE, DIMETHYL-; TOLUENE;  
BENZENE, METHYL-; ETHYL ALCOHOL; ALCOHOL; BENZENE; PSEUDOCUMENE; 1,  
2,4-TRIMETHYL BENZENE; ETHYL BENZENE; BENZENE, ETHYL-; CYCLOHEXANE;  
NAPHTHALENE; MOTH FLAKES

## Section 15. Regulatory information

### Pennsylvania

The following components are listed: GASOLINE; BENZENE, DIMETHYL-; BENZENE, METHYL-; DENATURED ALCOHOL; BENZENE; PSEUDOCUMENE; BENZENE, ETHYL-; CYCLOHEXANE; NAPHTHALENE

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.  
ethylbenzene; naphthalene; cumene

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.  
toluene

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.  
Benzene

Other Prop 65 chemicals will result under certain conditions from the use of this material. For example, burning fuels produces combustion products including carbon monoxide, a Prop 65 reproductive toxin.

### Other regulations

#### Australia inventory (AICS)

At least one component is not listed.

#### Canada inventory

All components are listed or exempted.

#### China inventory (IECSC)

At least one component is not listed.

#### Japan inventory (ENCS)

At least one component is not listed.

#### Korea inventory (KECI)

At least one component is not listed.

#### Philippines inventory (PICCS)

At least one component is not listed.

#### Taiwan inventory (CSNN)

#### REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	2
Flammability	3
Physical hazards	0
Personal protection	X

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### National Fire Protection Association (U.S.A.)



### History

Date of issue/Date of revision

12/16/2014.

Date of previous issue

No previous validation.

Product name BP Unleaded Gasolines

Product code 12631

Page: 20/21

Version 1 Date of issue 12/16/2014.

Format US

Language ENGLISH

(US)

(ENGLISH)

## Section 16. Other information

### Key to abbreviations

ACGIH = American Conference of Industrial Hygienists  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS Number = Chemical Abstracts Service Registry Number  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OEL = Occupational Exposure Limit  
SDS = Safety Data Sheet  
STEL = Short term exposure limit  
TWA = Time weighted average  
UN = United Nations  
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

✓ Indicates information that has changed from previously issued version.

### Notice to reader

*All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.*

*The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.*

*It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.*

Product name BP Unleaded Gasolines

Product code 12631

Page: 21/21

Version 1 Date of issue 12/16/2014.

Format US

Language ENGLISH

(US)

(ENGLISH)

