

8/3/17

# ASHLAND

## SAFETY DATA SHEET

Page: 1

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland  
P.O. Box 2219  
Columbus, OH 43216

Regulatory Information Number 1-800-325-3751  
Telephone 614-790-3333  
Emergency telephone number 1-800-ASHLAND (1-800-274-5263)

Product name NAPA® PREM PERF AUTOMATIC TRANSMISSION FLUID

Product code NP75200

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance: liquid, red

CAUTION! MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN  
AND CAUSE IRRITATION.

#### Potential Health Effects

##### Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

##### Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

##### Skin contact

May cause slight skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

##### Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

##### Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

##### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

##### Symptoms

# ASHLAND

## SAFETY DATA SHEET

Page: 2

Revision Date: 07/30/2013  
Print Date: 2/7/2014  
MSDS Number: R0200299  
Version: 1.23

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

**Target Organs**  
No data

### Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact. This material is not listed as carcinogenic by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. Good industrial hygiene practices are recommended to minimize exposure.

### Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material. There are no data available for assessing risk to the fetus from maternal exposure to this material. Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=90-<=100%
MINERAL OIL		>=5-<10%
METHACRYLATE COPOLYMER		>=1.5-<5%

## 4. FIRST AID MEASURES

### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

### Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

### Ingestion

# ASHILAND<sup>®</sup>

## SAFETY DATA SHEET

Page: 3

NAPA<sup>®</sup> PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

### Notes to physician

**Hazards:** Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

**Treatment:** No information available. No hazards which require special first aid measures.

## 5. FIREFIGHTING MEASURES

### Suitable extinguishing media

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Water spray

### Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons

### Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification  
Combustible Liquid Class IIIB

## 6. ACCIDENTAL RELEASE MEASURES

# ASHLAND®

## SAFETY DATA SHEET

Page: 4

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

### Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

### Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

### Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### Other information

Comply with all applicable federal, state, and local regulations.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

### Storage

Store in a cool, dry, ventilated area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

MINERAL OIL			
NIOSH	Recommended exposure	5 mg/m3	Mist.
	limit (REL):		
NIOSH	Short term exposure limit	10 mg/m3	Mist.
	Permissible exposure	5 mg/m3	Mist.
OSHA Z1	limit		
	time weighted average	5 mg/m3	Inhalable fraction.
ACGIH			

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

# ASHILAND®

## SAFETY DATA SHEET

Page: 5

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

### Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

### Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

### Respiratory protection

Respiratory protection is not required under normal conditions of use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Colour	red
Odour	hydrocarbon-like
Flash point	> 390 °F / > 199 °C Cleveland open cup
Evapouration rate	(>)1 Ethyl Ether
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V) Calculated Explosive Limit
Vapour pressure	0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor Pressure
Density	0.862 g/cm3 @ 60.01 °F / 15.56 °C
	7.29 lb/gal @ 60.00 °F / 15.56 °C
Viscosity, kinematic	35.8 mm2/s

## 10. STABILITY AND REACTIVITY

### Stability

Stable.

### Conditions to avoid

None known.

### Incompatible products

Strong oxidizing agents

### Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

### Hazardous reactions

Product will not undergo hazardous polymerization.

# ASHLAND

## SAFETY DATA SHEET

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

Page: 6

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin absorption  
Skin contact  
Eye Contact  
Ingestion

#### Product

Acute oral toxicity : no data available  
Acute inhalation toxicity : no data available  
Acute dermal toxicity : no data available  
Skin corrosion/irritation : no data available  
Serious eye damage/eye irritation : no data available  
Respiratory or skin sensitisation : no data available

#### Components:

##### HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD 50 Rat: > 15 g/kg  
Acute dermal toxicity : LD 50 Rabbit: > 5 g/kg

### 12. ECOLOGICAL INFORMATION

Ecotoxicity

#### Product:

no data available

#### Components:

# ASHLAND

## SAFETY DATA SHEET

Page: 7

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

### HEAVY PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l  
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Species: Aquatic invertebrates

### Persistence and degradability

#### Product:

no data available

#### Components:

no data available

### Bioaccumulative potential

#### Product:

no data available

#### Components:

### HEAVY PARAFFINIC DISTILLATE:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

### Mobility in soil

#### Product:

no data available

#### Components:

no data available

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

# ASHLAND<sup>®</sup>

## SAFETY DATA SHEET

Page: 8

Revision Date: 07/30/2013  
 Print Date: 2/7/2014  
 MSDS Number: R0200299  
 Version: 1.23

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
 FLUID  
 NP75200

### 14. TRANSPORT INFORMATION

REGULATION	ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
U.S. DOT - ROAD		Not dangerous goods				
U.S. DOT - RAIL		Not dangerous goods				
U.S. DOT - INLAND WATERWAYS		Not dangerous goods				
TRANSPORT CANADA - ROAD		Not dangerous goods				
TRANSPORT CANADA - RAIL		Not dangerous goods				
TRANSPORT CANADA - INLAND WATERWAYS		Not dangerous goods				
INTERNATIONAL MARITIME DANGEROUS GOODS		Not dangerous goods				
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO		Not dangerous goods				
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER		Not dangerous goods				
MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES		Not dangerous goods				

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### 15. REGULATORY INFORMATION



# ASHLAND®

## SAFETY DATA SHEET

Page: 9

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
FLUID  
NP75200

Revision Date: 07/30/2013

Print Date: 2/7/2014

MSDS Number: R0200299

Version: 1.23

### California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

### SARA Hazard Classification

SARA 311/312 Classification

No SARA Hazards

### SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE	64742-54-7
MINERAL OIL	
AUTOMATIC TRANSMISSION FLUID ADDITIVE	
METHACRYLATE COPOLYMER	

### Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE	64742-54-7
MINERAL OIL	
AUTOMATIC TRANSMISSION FLUID ADDITIVE	

### Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Japan. ENCS - Existing and New Chemical Substances Inventory	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current.

# ASHLAND

## SAFETY DATA SHEET

Revision Date: 07/30/2013  
 Print Date: 2/7/2014  
 MSDS Number: R0200299  
 Version: 1.23

NAPA® PREM PERF AUTOMATIC TRANSMISSION  
 FLUID  
 NP75200

applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
 ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level  
 CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System