

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom2012

Date of issue: 9/24/2019

Revision date: 9/24/2019

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name

: PB Penetrating Catalyst

Product code

: 16-PB, 8-PB, 8-PBS, PB-TS, 20-PB, 26-PB, 16-PB-DS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

: Penetrant

1.3. Details of the supplier of the safety data sheet

Manufacturer

The Blaster Corporation 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA T (216) 901-5800 - F (216) 901-5801 www.blastercorp.com

1.4. Emergency telephone number

Emergency number

: ChemTel 800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 2

Gases under Pressure (Dissolved gas)

Asp. Tox. 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



 \Diamond



GHS02

Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatalif swallowed and enters airways.

Precautionary statements (GHS-US)

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

3.2. Mixtures

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	50 - 60
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	20 - 30
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS No) 64742-52-5	20 - 30
Carbon dioxide	(CAS No) 124-38-9	1 - 4

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists. Remove affected clothing and wash all exposed skin area with mild soap and water, followed

First-aid measures after eye contact

: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion

: IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory tractirritation.

Symptoms/injuries after skin contact

: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the

skin.

Symptoms/injuries after eye contact

: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatmentneeded

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Carbon dioxide, dry chemical, halons or foam.

Unsuitable extinguishing media

: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon and oxides of nitrogen.

Explosion hazard

: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity

: No dangerous reaction known under conditions of normal use.

5.3. Advice for firefighters

Firefighting instructions

: DO NOT fight fire when fire reaches explosives. Evacuate area. Exercise caution when fighting any chemical fire.

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures

: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

: Equip cleanup crew with proper protection.

9/24/2019 EN (English) 2/7



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate source

: Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter

waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not spray on an open flame or other ignition source. Keep away from sources of ignition-

No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapour or spray. When using do not eat, drink or smoke. Use only

outdoors or in a well-ventilated area. Do not pierce or burn, even after use.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including anyincompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should befollowed.

Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/

122 °F. Store away from direct sunlight or other heat sources. Keep in fireproofplace.

Storage area : Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distilla	tes, hydrotreated light (64742-47-8)		
Not applicable	,		
Solvent naphtha,	petroleum, heavy aromatic (64742-94-5)		
Not applicable			
Distillates, petrole	eum, hydrotreated heavy naphthenic (64742-52-5		
Not applicable			
Carbon dioxide (1	24-38-9)		
ACGIH	ACGIH TWA (ppm)	5000 ppm	
ACGIH	ACGIH STEL (ppm)	30000 ppm	

8.2. Exposure controls

OSHA

OSHA

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

OSHA PEL (TWA) (mg/m3)

OSHA PEL (TWA) (ppm)

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

9000 mg/m³

5000 ppm

safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands

carefully before eating or smoking. Handle according to established industrial hygiene and

safety practices.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid Physical state : Clear. Aerosol. Appearance Colour : Orange Odour : Characteristic : No data available Odour threshold No dataavailable pH : No data available Melting point : No data available Freezing point : 356 °F (180 °C) Boiling point : > 141 °F (> 61 °C) Flash point : No data available Relative evaporation rate (butylacetate=1) Flammability (solid, gas) : Flammableaerosol. : No data available Vapour pressure

Relative density : 0.9

Solubility : No data available Partition coefficient n-octanol/water No data available No data available Auto-ignition temperature No data available Decomposition temperature No data available Viscosity, kinematic No data available Viscosity, dynamic No data available Explosive limits No data available Explosive properties No dataavailable Oxidising properties

9.2. Other information

Relative vapour density at 20 °C

Heat of Combustion : 45.8 kJ/g
Flame Projection : 0 inches
Flashback : None

SECTION 10: Stability and reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

No data available

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatiblematerials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon and oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

9/24/2019 EN (English) 4/7



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

PB Penetreating Catalyst	
LD50 oral rat	> 2000 mg/kg (Calculated Acute Toxicity Estimate)
LD50 dermal rabbit	> 2000 mg/kg (Calculated Acute Toxicity Estimate)
LC50 inhalation rat	> 5 mg/l/4h (Calculated Acute Toxicity Estimate)
Petroleum distillates, hydrotreat	ed light (64742-47-8)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Solvent naphtha, petroleum, hea	vy aromatic (64742-94-5)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat	> 590 mg/m³ (Exposure time: 4 h)

 Skin corrosion/irritation
 : Notclassified.

 Serious eye damage/irritation
 : Notclassified.

 Respiratory or skin sensitisation
 : Notclassified.

 Germ cell mutagenicity
 : Notclassified.

Carcinogenicity : Notclassified.

Reproductive toxicity : Not classified.

Specific target organ toxicity(single exposure) : Notclassified.

Specific target organ toxicity (repeated : Not classified.

exposure)

Aspiration hazard

: May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries afterskin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the

skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking andtear

production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and

cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotreated light (647	42-47-8)	
LC50 fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
Solvent naphtha, petroleum, heavy aromatic	(64742-94-5)	
LC50 fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
Distillates, petroleum, hydrotreated heavy na	aphthenic (64742-52-5)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

Persistence and degradability

PB Penetreating Catalyst	
Persistence and degradability	Not established.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Bioaccumulative potential

PB Penetreating Catalyst	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated light	(64742-47-8)
BCF fish 1	61 - 159
Solvent naphtha, petroleum, heavy aron	natic (64742-94-5)
BCF fish 1	61 - 159
Partition coefficient n-octanol/water	2.9 - 6.1

BCF fish 1

(no bioaccumulation)

Mobility in soil 12.4.

No additional information available

Other adverse effects

: No known effects from this product. Effect on the global warming

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

: This material must be disposed of in accordance with all local, state, provincial, and federal Waste disposal recommendations

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transportinformation

DOT, IATA & IMO

: UN1950 UN-No.

Proper Shipping Name : AEROSOLS, flammable, limited quantities

: 2.1 Class

Hazard labels



Other information : No supplementary information available.

: Do not handle until all safety precautions have been read and understood. Special transport precautions

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of

15.3. alifornia to cause cancer, developmental and/or reproductive harm

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Naphthalene (91-20-3) U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	5.8 μg/day

Carbon dioxide (124-38-9)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Otherinformation

Date of issue : 9/24/20198
Revision date : 9/24/2019
Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

