



PRESS-SEAL CORPORATION

P.O. Box 10482 - Fort Wayne, IN 46852
2424 West State Blvd. - Fort Wayne, IN 46808
Toll Free: 800-348-7325
Office: 260-436-0521
sales@press-seal.com
www.press-seal.com

Printing Date 07/16/2015
Revision Date 04/22/2015

Safety Data Sheet
acc. to OSHA HCS
Revision Number 2

1 Identification

- **Product identifier**
- **Trade name:** E-Z Primer
- **Article number:** 730694-10588
- **Relevant identified uses of the substance or mixture.** Primer
- **Application of the substance / the mixture** Priming
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Royal Adhesives & Sealants, LLC
4401 Page Avenue. P. O. Box 457
Michigan Center, MI 49254
Information Phone Number: 517-764-0334
- **Information department:** Environment protection department.
- **Emergency telephone number:**
ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

• **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS08

- **Signal word** Danger
- **Hazard statements**
Highly flammable liquid and vapor.
May cause cancer.
May be fatal if swallowed and enters airways.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 1)

Wear protective gloves / eye protection / face protection.
 Ground/bond container and receiving equipment.
 Keep container tightly closed.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 If swallowed: Immediately call a poison center/doctor.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store locked up.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Classification system:**

• **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 3
 Reactivity = 0

• **HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	3
PHYSICAL HAZARD	0

Health = 2
 Fire = 3
 Physical Hazard = 0

• **Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

• **Chemical characterization: Mixtures**

• **Description: Mixture**

• **Hazardous components:**

64742-89-8	Solvent naphtha (petroleum), light aliph.(VM&P)	50-100%
1333-86-4	Carbon black	2.5-10%
1332-58-7	Kaolin	2.5-10%
1309-48-4	magnesium oxide	≤0.09%

• **Additional information:**

All concentrations are in percent by weight unless the ingredient is a gas. Gas concentrations are in percent by volume. Any pigments or fillers in this product which may be considered "Hazardous" are potentially hazardous only if inhaled as an airborne dust. Exposure by these ingredients as used in sealants, putties, bedding compounds and non-sprayable products is highly unlikely. For the wording of the listed risk phrases refer to section 15.

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 2)

4 First-aid measures

• Description of first aid measures

• After inhalation:

Call a doctor immediately.

Overexposure, remove to fresh air and seek medical attention.

• After skin contact:

Wipe excess from skin.

Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.

• After swallowing:

Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Call a doctor immediately.

Seek medical treatment.

• Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

• Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

• Extinguishing media

• Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

• For safety reasons unsuitable extinguishing agents:

Water

Water and water with full jet

• Special hazards arising from the substance or mixture No further relevant information available.

• Advice for firefighters

• Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

• Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

• Handling:

• Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Open containers in a well ventilated area and avoid breathing headspace vapors.

Open and handle receptacle with care.

Prevent formation of aerosols.

• Information about protection against explosions and fires:

Keep container closed when not in use.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

• Conditions for safe storage, including any incompatibilities

• Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.

• Information about storage in one common storage facility: Store away from oxidizing agents.

• Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

• Control parameters

• Components with limit values that require monitoring at the workplace:

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³
*inhalable fraction

1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 2* mg/m³
E; as respirable fraction

1309-48-4 magnesium oxide

PEL Long-term value: 15* mg/m³
fume; *total particulate

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 4)

TLV Long-term value: 10* mg/m³
*as inhalable fraction

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Black

· **Odor:** Solvent-like

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 5)

· Change in condition	
Melting point:	Undetermined.
Boiling point:	85 °C (185 °F)
· Flash point:	7.8 °C (46 °F)
· Flammability (solid, gaseous):	Flammable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Flammable limits:	
Lower:	1.2 Vol %
Upper:	Not Determined
· Vapor pressure:	38mm Hg (20 °C)
· Specific gravity at 20 °C (68 °F):	0.84 g/cm ³ (7.01 lbs/gal)
· Relative density	Not determined.
· Vapour density at 20 °C (68 °F)	3.6 g/cm ³ (30.042 lbs/gal)
· Evaporation rate at 20 °C (68 °F)	3.5
· Solubility in / Miscibility with Water:	Slightly soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	77.0 %
Solids content:	16.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flames, sparks.
- **Incompatible materials:** Reacts with strong oxidizing agents.
- **Hazardous decomposition products:** No dangerous decomposition products known.

— USA —

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 6)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· Primary irritant effect:

· on the skin: Skin irritant.

· on the eye: Vapors may be irritating to the eyes.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity: Expected to be harmful to aquatic organisms.

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

At present there are no ecotoxicological assessments.

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

Disposal must be made according to official regulations.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2



Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 7)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number
- DOT, ADR, IMDG, IATA UN1133
- UN proper shipping name
- DOT Adhesives
- ADR 1133 Adhesives
- IMDG, IATA ADHESIVES
- Transport hazard class(es)
- DOT
- 
- Class 3 Flammable liquids
- Label 3
- ADR, IMDG, IATA
- 
- Class 3 Flammable liquids
- Label 3
- Packing group
- DOT, ADR, IMDG, IATA II
- Environmental hazards: Not applicable.
- Special precautions for user Warning: Flammable liquids
- Danger code (Kemler): 33
- EMS Number: F-E,S-D
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- UN "Model Regulation": UN1133, Adhesives, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 8)

• **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

• **Proposition 65**

• **Chemicals known to cause cancer:**

64742-89-8 Solvent naphtha (petroleum), light aliph.(VM&P)

1333-86-4 Carbon black

• **Chemicals known to cause reproductive toxicity:**

None of the ingredients is listed.

• **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

• **Carcinogenicity categories**

• **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

• **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4 Carbon black

A4

1332-58-7 Kaolin

A4

1309-48-4 magnesium oxide

A4

• **MAK (German Maximum Workplace Concentration)**

1333-86-4 Carbon black

3B

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 Carbon black

• **National regulations:**

• **Information about limitation of use:** Use by properly trained workers recommended.

• **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

• **Department issuing SDS:** Environment protection department.

• **Creation Date:** 11/22/2011

• **Date of preparation / last revision** 07/16/2015 / 1

• **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing Date 07/16/2015

Revision Number 2

Revision Date 04/22/2015

Trade name: E-Z Primer

(Contd. of page 9)

WHMIS: Workplace Hazardous Materials Information System (Canada)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Carc. 1B: Carcinogenicity, Hazard Category 1B

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

USA