STIHL HP (HIGH PERFORMANCE) 2-CYCLE ENGINE OIL

01/18/2021

Packaged for Stihl Incorporated, 536 Viking Drive, Virginia Beach, VA 23452



Safety Data Sheet Conforms to HCS 2012 (29 CFR 1910.1200)

| Section 1. Identif | ication |
|-------------------------|---|
| Product identifier | |
| Product Name: | STIHL HP (High Performance) 2-Cycle Engine Oil |
| Other names: | F3E |
| Part/Product Number(s): | 0781-319-8008, 0781-319-8009, 0781-319-8010, 0781-319-8014 , 0781-319-8015 , 0781-319-8016 , 0781-319-8044 , 0781-319-8045 , 0781-319-8049 , 0781-319-8051, 7010-871-0208 , 7010-871-0177 |
| Material Use: | 2-cycle engine fuel additive |
| Uses advised against: | Not for use in non-2-cycle engines |
| Manufacturer: | Omni Specialty Packaging, LLC 10399 Hwy 1 South Shreveport, LA 71115 1-318-524-1100 |
| Issuing date: | May 21, 2015 |
| Revision date: | February 28, 2018 |
| Revision number: | 003 |
| Company contact: | OMNI EHS Department: E-Mail: <u>sds@osp.cc;</u> Contact phone: 318-524-1100 (Monday-Friday, 8:00 AM – 4:00 PM, CST) |
| In case of emergency: | CHEMTREC: Within USA and Canada: 1 (800) 424-9300 (24/7) CHEMTREC: Outside USA and Canada: +1 703-527-3887 (24/7) |

Section 2. Hazards Identification

| OSHA/HCS Status: | This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). | | | |
|---|--|--|--|--|
| Classification of the Substance or Mixture: Not classified | | | | |
| GHS Label Elements | | | | |
| Hazard pictograms: | | | | |
| Signal word: | None | | | |
| Hazard statement: | None | | | |
| Precautionary statemen | <u>its</u> | | | |
| General: | Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. | | | |
| Prevention: | Not applicable | | | |
| Response: | Not applicable | | | |
| Storage: | Not applicable | | | |
| Disposal: | Not applicable | | | |
| Hazards not otherwise classified (HNOC): Defatting to the skin. | | | | |
| Other information: | Product diluted with gasoline must be handled with the same precautions used for gasoline. Before mixing, the Safety Data Sheet for gasoline should be consulted for any precautionary measures necessary. | | | |

Section 3. Composition/Information on Ingredients

Petroleum mineral oil lubricant base stock with proprietary performance additives mixture.

| Components Name | CAS number | Weight %* |
|--|-------------|-----------|
| Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15-C50) | Various | 85 – 95 |
| 2-Cycle Engine Oil Additives Mixture | Proprietary | 5 – 15 |

This product does not contain known hazardous materials at the \geq 1% level or known carcinogens at the \geq 0.1% level as defined by 29 CFR 1910.1200.

* The exact percentage of composition has been withheld as a trade secret.

| Section 4. First Aid Measures | | |
|---|--|--|
| Description of necessary first aid measures | | |
| General Advice: | No specific first aid measures are required. Get medical attention if irritation develops and persists. | |
| Eye contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if irritation develops and persists. | |
| Skin contact: | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation or allergic reaction develops and persists. | |
| Inhalation: | In case of inhalation of decomposition products in a fire, symptoms may be delayed. If inhaled, remove to fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur. | |
| Ingestion: | Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician. | |
| Protection of first-aiders: | No action shall be taken involving any personal risk or without suitable training. Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). | |
| | nd effects, both acute and delayed ailed information on health effects and symptoms. | |
| Most Important Symptoms and Effects: P | ersonnel with pre-existing skip disorders should avoid contact with this product. Under normal use | |

| Most Important Symptoms and Effects: | Personnel with pre-existing skin disorders should avoid contact with this product. Under normal use conditions, no adverse effects to health are known. |
|---|--|
| Eye contact: | Not expected to cause prolonged or significant eye irritation. |
| Skin contact: | Contact with skin is not expected to cause prolonged or significant irritation. Contact with skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. |
| Inhalation: | Not expected to be harmful if inhaled. Contains petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficult breathing. |
| Ingestion: | Not expected to be harmful if swallowed. |
| Note to physician: | Treat symptomatically. |

| Section 5. Fire-Fighting Measures | | |
|---|---|--|
| Uniform Fire Code: | Class IIIB | |
| Flash Point: | 222°C (432°F) | |
| Extinguishing Media | | |
| Suitable Media: | In case of fire, use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water fog, alcohol resistant foam, dry chemical, carbon dioxide (CO2) extinguisher or spray. | |
| Unsuitable Media: | CAUTION: Use of water spray when fighting fire may be inefficient. | |
| Specific Hazards Arising from the Chemical: | Keep product and empty container away from heat and sources of ignition as product will burn. Contact with strong oxidizers may cause fire. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be contained, prevented from being discharged to any waterway, sewer or drain and disposed of in accordance with local regulations. | |
| Hazardous Combustion Products: | Combustion products may include the following: Carbon dioxide (CO2) Carbon monoxide (CO), and Nitrogen oxides. | |
| Protection of Fire Fighters: | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. | |

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

| For non-emergency personnel: | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. |
|------------------------------|--|
| For emergency responders: | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. See also the information in "For non-emergency personnel". |
| Environmental precautions: | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). See Section 12 for ecological information. |

Methods and materials for containment and cleaning up

Small Spills: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spills: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

NOTE: If RQ (Reportable Quantity) is exceeded or if spills enter a body of water, report immediately to the USEPA's National Response Center at (800) 424-8802. Check with your local and state regulators regarding their reporting requirements.

Section 7. Handling and Storage Precautions for safe handling Protective measures: Eye protection and face shield should be used if material is used under conditions that increase the chances of splattering. Put on appropriate personal protective equipment (see Section 8). Keep out of reach of children.

NOTE: Product diluted with gasoline must be handled with the same precautions used for gasoline. Before mixing, the Safety Data Sheet for gasoline should be consulted for any precautionary measures necessary.

Advice on general Do not get in eyes, on skin or on clothing. Eating, drinking and smoking should be occupational hygiene: prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Conditions for safe storage, Store in accordance with local regulations. Store in original container protected from Including any incompatibilities: direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials, strong oxidizing agents (see Section 10) and food and drink. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Avoid contaminating soil or releases into sewage or drainage systems and bodies of water.

Section 8. Exposure Controls/Personal Protection

Control parameters Occupational Exposure Limits

| | ACGIH | | OSHA | | NIOSH | |
|---|--|---|---|--|--|-------------------------|
| Chemical name | TLV | STEL | PEL | STEL | TWA | Ceiling |
| Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15-C50) | 5 mg/m3 (mist) | 10 mg/m3 (mist) | 5 mg/m3 (mist) | _ | <u>. </u> | _ |
| Appropriate engineering controls: | Good general venti contaminants. Eme | | | | er exposure | to airborne |
| Environmental exposure controls: | Emissions from ve they comply with t cases, fume scrub equipment will be | he requirement bers, filters or | s of environm engineering m | ental protec odifications | tion legislat to the proc | ion. In so ess |
| ndividual protection measures | | | | | | |
| Hygiene measures: | Wash hands, forea before eating, smo period. Appropriate contaminated cloth eyewash stations | oking and using techniques s hing. Wash cor | the lavatory hould be used ntaminated clo | and at the e to remove othing before | nd of the wo potentially e reusing. E | orking Ensure tha |
| Eye/Face Protection: | Wear safety glasse some conditions. | es with side shie | elds. A face sh | nield may be | necessary ι | under |
| Skin and Body Protection | | | | | | |
| Hand protection: | Wear protective gl chemical resistant or Standard Opera | gloves. Recor | mmended: Nitr | ile gloves. C | Consult your | superviso |
| Body protection: | No protective equip tasks, personal pro task being perform | tection equipm | ent for the bod | l use condition y should be | ons. For no selected bas | n-routine sed on the |
| Other skin protection: | Appropriate footwe | ar and any add | itional skin pro | tection meas | sures should | d be |
| | P | age 4 of 8 | | | | |

selected based on the task being performed and the risks involved.

Respiratory protection:

No respiratory protection is normally required. If user operation generates an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from measured concentrations of this material. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Section 9. Physical and Chemical Properties

| Appearance | (Typical or Target) |
|---|---|
| Physical State: | Liquid |
| Color: | Blue |
| Odor: | Petroleum distillates |
| Odor threshold: | Not available |
| pH: | Not applicable |
| Boiling Point: | Not available |
| Flash Point (Closed cup): | 222°C (432°F) (Typical or Target) |
| Pour Point: | -25°C (-13°F) (Typical or Target) |
| Evaporation rate (Butyl acetate = 1): | Not available |
| Flammability (solid, gas): | Not applicable. Based on - Physical state |
| Flammable) Limit in Air | Not available |
| Vapor pressure: | Not available |
| Vapor density (Air = 1): | >1 |
| Relative density: | 0.8820 - 0.8990 g/l at 15°C (Typical or Target) |
| Solubility: | In soluble in water |
| Partition coefficient (n-Octanol/water): | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition temperature: | Not available |
| Viscosity – Kinematic (cSt (mm2/s)@ 40°C): | 85 to 100 |
| Viscosity - Kinematic (cSt (mm2/s) @ 100°C) | :10.3 to 12 |
| VOC %: | <0.026% |
| | |

Section 10. Stability and Reactivity

| Reactivity: | Not reactive under normal storage conditions |
|-------------------------------------|--|
| Chemical stability: | Stable under normal storage conditions |
| Possibility of hazardous reactions: | None under normal processing. |
| Hazardous polymerization: | Hazardous polymerization does not occur. |
| Conditions to avoid: | Heat, flames and sparks. |
| Incompatible materials: | Oxidizing agents, Halogens, Halogenated compounds |
| Hazardous decomposition products: | May include: Fumes, Oil vapors, Smoke, Carbon Oxides (including carbon monoxide and carbon dioxide), Aldehydes, Nitrogen oxides, and incomplete combustion products. |

Section 11. Toxicological Information Information on toxicological effects Basis for Assessment: Information given is based on product data, a knowledge of the components and the toxicity of similar products. Likely Routs of Exposure: Exposure may occur via skin absorption, skin or eye contact, inhalation, ingestion.

Substance/Mixture

| Acute Toxicity | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|-------------------|----------------------|----------------------------|
| Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15- C50) Mixture - Typical | >2000 mg/Kg (rat) | >2000 mg/Kg (rabbit) | >2.18 mg/L (rat) 4h (mist) |

STIHL HP (HIGH PERFORMANCE) 2-CYCLE ENGINE OIL

| Aspiration hazard: | Not expected to be an aspiration hazard. |
|--|---|
| Skin Corrosion/Irritation: | No known significant effects or critical hazards. |
| Serious Eye Damage/Irritation: | No known significant effects or critical hazards. |
| Skin Sensitization: | No known significant effects or critical hazards. |
| Respiratory Sensitization: Specific Target Organ Toxicity | No known significant effects or critical hazards. |
| (Single Exposure) - STOT-SE: Specific Target Organ Toxicity | No known significant effects or critical hazards. |
| (Repeated Exposure) – STOT-RE: | No known significant effects or critical hazards. |
| Carcinogenicity: | No known significant effects or critical hazards. |
| Germ Cell Mutagenicity: | No known significant effects or critical hazards. |
| Reproductive Toxicity: | No known significant effects or critical hazards. |
| | |

Information on Toxicity Effects of Compounds

Lubricant Base Mineral Oil (Petroleum)

Mineral oils are known to cause cancer because of carcinogenic components (e.g. Benzene). The lubricant base mineral oils in this product have been highly refined by a variety of processes including severe solvent extraction, severe hydro cracking or severe hydro treating to reduce aromatics and improve performance characteristics. The oils in this product meet the IP-346 criteria of less than 3 percent PHA's and are not considered to be a carcinogen by the International Agency for Research on Cancer.

None of the oils in this product require a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IRAC) as: carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

2-Cycle engine oils mix with gasoline:

2-cycle engine oils diluted with gasoline must be handled with the same precautions used for gasoline. Before mixing, the Safety Data Sheet for gasoline should be consulted for any precautionary measures necessary.

Section 12. Ecological Information

The information is based on data available for the material, the components of the material, and similar materials.

| Ecotoxicity: | toxicity: No testing has been performed by the manufacturer. Ecotoxicity hazard is based on an evaluation of data for the components or a similar material. Not expected to be harmful to aquatic organisms. | | |
|----------------------------------|--|---|--|
| Mobility: | | Base oil component – Low solubility and floats and is expected to migrate from water to land. Expected to partition to sediment and wastewater solids. | |
| Soil/water p coefficient | | Not available. | |
| <u>Persistence</u> Biodegrada | and degradation tion: | The material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. | |
| <u>Bioaccumu</u> Bioaccumu | lative potential lation: | This product is not expected to bioaccumulate through food chain in the environment. | |
| Other adve | rse effects: | No known significant effects or critical hazards. | |
| Other ecold | ogical information: | Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired. | |

Section 13. Disposal Considerations

Disposal recommendations based on material supplied.

| Waste treatment methods: | This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Consult the appropriate state, regional, or local regulations for additional requirements. The generation of waste should be avoided or minimized wherever possible. |
|--------------------------|--|
| Product waste: | Significant quantities of waste product residues should not be disposed of via the sanitary sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Incineration or landfill should only be considered when recycling is not feasible. Oil collection services are available for used oil recycling. |
| Contaminated packaging: | Empty containers or liners may retain some product residues and could pose a potential fire and explosion hazard. Do not cut, puncture, or weld containers. |
| Other information: | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

Section 14. Transport Information

Petroleum lubricating oil - Not regulated. General information:

| | DOT Classification | IMDG | IATA |
|------------------|--------------------|---------------|---------------|
| Stihl HP 2-Cycle | Not Regulated | Not Regulated | Not Regulated |

Special precautions for user:

Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory Information

| United States Inventory (TSCA 8b): <u>SARA 302/304:</u> | | All components are listed or exempted. No products were found. | | |
|--|---|--|---|--|
| <u>SARA 311/312</u> : SARA 313: | | Immediate (Acute) Health Effects: Delayed (Chronic) Health Effects: Fire Hazard: Sudden Release of Pressure Hazard: Reactivity Hazard: | No No No | |
| <u>54(4315</u> . | The follow None | ing components of this material are four | nd on the EPCRA 313 list: | |
| Supplier notification: | Supplier notification: This product does not contain any hazardous ingredients at or above regulated thresholds. | | | |
| CWA (Clean Water Act): | | uct does not contain any substances reg ter Act (40 CFR 122.21 and 40 CFR 122 | A set of the set of | |
| CERCLA: | This material, as supplied, does not contain any substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302). | | | |
| <u>State Regulations</u> Massachusetts: New Jersey: Pennsylvania: | None of th | ne components are at or above regulated ne components are at or above regulated ne components are at or above regulated | d thresholds. | |

STIHL HP (HIGH PERFORMANCE) 2-CYCLE ENGINE OIL

California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer. Ethylbenzene - <0.1

Canada WHMIS Hazard Class:

Not classified.

International Chemical Inventories:

All components comply with the following chemical inventory requirements: DSL (Canada)

Section 16. Other Information

| NFPA Rating: | Health Hazard – 1 | Flammability – 1 | Instability/Reactivity – 0 |
|--------------|-------------------|------------------|----------------------------|
| HMIS Rating: | Health Hazard – 1 | Flammability – 1 | Physical Hazards – 0 |

(NFPA & HMIS Hazard Rating Key: 0 - Minimum Hazard; 1 - Slight Hazard; 2 - Moderate Hazard; 3 - High Hazard; 4 - Extreme Hazard; * - Chronic Hazard Indicator, & PPE - Personal Protective Equipment Index A to L. These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS or Hazardous Material Identification System).

Key to abbreviations:

OSHA = Occupational Safety and Health Administration

ACGIH= American Conference of Industrial Hygienists

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service Registry Number

cSt = Centistroke (mm2/s)

GHS = Global Harmonized System of Classification and Labeling Of Chemicals.

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient OEL = Occupational Exposure Limit SDS = Safety Data Sheet STEL = Short term exposure Limit

UN = United Nations

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transportation of Dangerous Goods

Prepared By: OMNI Specialty Packaging EH&S Department

Revision Date: February 28, 2018

Status: Final

Revision Note: Revision 003 – Three year review and update.

Consumer Product Improvement Act of 2008, General Conformity Certification

For Consumer Product Packages: This product has been evaluated and is certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission. Where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No testing is required to certify compliance with the provisions. The date of the manufacturing is stamped on the product container.

<u>Disclaimer</u>

All reasonably practicable steps have been taken to ensure the information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

End of Safety Data Sheet