 Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**

Trade name : Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825)	Emergency telephone number 1-800-VALVOLUME (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-8326-825) Product Information 1-800-TEAMVAL (1-800-8326-825)
--	---

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.2407

SECTION 4. FIRST AID MEASURES


General advice : No hazards which require special first aid measures.

	Page: 2
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.

 Valvoline TM	Page: 3
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline TM PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
nitrogen oxides (NO_x)

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.


SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Components	CAS-No.
Benzenesulfonic acid, C10-60-	90194-32-4

 Valvoline ™	Page: 4
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

alkyl derivs., sodium salts

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available


Flash point : > 390 °F / > 199 °C
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)
Calculated Explosive Limit

Lower explosion limit : 1 %(V)


 Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

Vapour pressure	Calculated Explosive Limit : 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8785 g/cm3 (15.6 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 80 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

 Valvoline ™	Page: 6
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version 1.2

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information

Product:


Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

 Valvoline		Page: 7
SAFETY DATA SHEET		Revision Date: 07/13/2017
		Print Date: 10/30/2018
		SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil		Version: 1.2
VV159		

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C


Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

 Valvoline		Page: 8
SAFETY DATA SHEET		Revision Date: 07/13/2017
		Print Date: 10/30/2018
		SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil		Version: 1.2
VV159		

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION
**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**


Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

	Page: 9
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

IECSC : Low volume exemption

PICCS : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/13/2017


NFPA:	HMIS III:						
<p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td><td>0</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H319 Causes serious eye irritation.

	Page: 10
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2


Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

 Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/30/2018
	SDS Number: R0178048
Valvoline™ PREMIUM CONVENTIONAL SAE 30 Motor Oil VV159	Version: 1.2

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System

