SAFETY DATA SHEET





Nonflammable Gas Mixture: Carbon Monoxide / Hydrogen Sulfide / Methane / Nitrogen / Oxygen

Section 1. Identification

GHS product identifier

: Nonflammable Gas Mixture: Carbon Monoxide / Hydrogen Sulfide / Methane / Nitrogen /

Oxygen

Other means of identification

: Not available.

Product type

: Gas.

Product use

: Synthetic/Analytical chemistry.

SDS#

: 012738

Supplier's details

: Gasco Affiliates, LLC

320 Scarlet Blvd. Oldsmar, FL 34677

Email: info@gascogas.com

Tel: (800) 910-0051

Fax Number: (866) 755-8920

24-hour telephone

: Inside the US: 1-833-723-3267 (Chemtrec, 24 hours) Outside the US: 1-703-527-3887

(Chemtrec, 24 hours)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

: GASES UNDER PRESSURE - Compressed gas

GHS label elements

Hazard pictograms

Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.

Precautionary statements

General

: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Do not depend on odor to detect presence of gas.

Prevention

: Not applicable.

Response

: Not applicable.

Storage

: Protect from sunlight. Store in a well-ventilated place.

Disposal

: Not applicable.

Hazards not otherwise

classified

: In addition to any other important health or physical hazards, this product may displace

oxygen and cause rapid suffocation.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

Product code

: 012738

| Ingredient name | % | CAS number |
|------------------|-----------------|------------|
| Nitrogen | 77.159 - 99 | 7727-37-9 |
| oxygen | 1 - 19.5 | 7782-44-7 |
| methane | 0.0001 - 3 | 74-82-8 |
| hydrogen sulfide | 0.0001 - 0.2499 | 7783-06-4 |
| carbon monoxide | 0.0001 - 0.0999 | 630-08-0 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eve contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: As this product is a gas, refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Contact with rapidly expanding gas may cause burns or frostbite.

Inhalation : No known significant effects or critical hazards.

Skin contact: Contact with rapidly expanding gas may cause burns or frostbite.Frostbite: Try to warm up the frozen tissues and seek medical attention.

Ingestion : As this product is a gas, refer to the inhalation section.

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed.

Section 4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Immediately contact emergency personnel. Stop leak if without risk.

Large spill

: Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid breathing gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F). Keep container tightly closed and sealed until ready for use. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------|--|
| Nitrogen | ACGIH TLV (United States, 1/2021). Oxygen |
| | Depletion [Asphyxiant]. |
| oxygen | None. |
| methane | ACGIH TLV (United States, 1/2021). Oxygen |
| | Depletion [Asphyxiant]. Explosive potential. |
| hydrogen sulfide | ACGIH TLV (United States, 1/2021). |
| | STEL: 5 ppm 15 minutes. |
| | TWA: 1 ppm 8 hours. |
| | NIOSH REL (United States, 10/2020). |
| | CEIL: 15 mg/m³ 10 minutes. |
| | CEIL: 10 ppm 10 minutes. |
| | OSHA PEL 1989 (United States, 3/1989). |
| | STEL: 21 mg/m³ 15 minutes. |
| | STEL: 15 ppm 15 minutes. |
| | TWA: 14 mg/m³ 8 hours. |
| | TWA: 10 ppm 8 hours. |
| | OSHA PEL Z2 (United States, 2/2013). |
| | AMP: 50 ppm 10 minutes. |
| | CEIL: 20 ppm |
| carbon monoxide | California PEL for Chemical Contaminants (|
| | Table AC-1) (United States). |
| | PEL: 25 ppm 8 hours. |
| | CEIL: 200 ppm |
| | ACGIH TLV (United States, 1/2021). |
| | TWA: 25 ppm 8 hours. |
| | TWA: 29 mg/m³ 8 hours. |
| | OSHA PEL 1989 (United States, 3/1989). |
| | TWA: 35 ppm 8 hours. |
| | TWA: 40 mg/m³ 8 hours. |
| | CEIL: 200 ppm |
| | CEIL: 229 mg/m³ |
| | NIOSH REL (United States, 10/2020). |
| | TWA: 35 ppm 10 hours. |
| | TWA: 40 mg/m³ 10 hours. |
| | CEIL: 200 ppm |
| | CEIL: 229 mg/m ³ |
| | OSHA PEL (United States, 5/2018). |
| | TWA: 50 ppm 8 hours. |
| | TWA: 55 mg/m³ 8 hours. |

Section 8. Exposure controls/personal protection

- Appropriate engineering controls
- **Environmental exposure** controls
- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures
- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection
- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- **Body protection**
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection
- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state

: Gas.

Color

: Not available.

Odor

pH

: Not available.

Odor threshold

: Not available.

: Not applicable.

Melting point

: -187.6°C (-305.7°F) This is based on data for the following ingredient: methane.

Weighted average: -210.53°C (-347°F)

Boiling point

: Not available.

Critical temperature

: Lowest known value: -146.95°C (-232.5°F) (nitrogen).

Flash point

: Not applicable.

Evaporation rate

: Not available. : Not available.

Flammability (solid, gas) Lower and upper explosive

: Not available.

(flammable) limits

Section 9. Physical and chemical properties

Gas Density (lb/ft 3)

: Weighted average: 0.07

Relative density

: Not applicable.

Solubility

: Not available.

Solubility in water

: Not available.

Partition coefficient: n-

: Not applicable.

octanol/water

: Not available.

Auto-ignition temperature Decomposition temperature: Not available.

Flow time (ISO 2431)

: Not available.

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: No specific data.

Incompatible materials

: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|----------------------|---------|----------|----------|
| hydrogen sulfide | LC50 Inhalation Gas. | Rat | 712 ppm | 1 hours |
| carbon monoxide | LC50 Inhalation Gas. | Rat | 3760 ppm | 1 hours |

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Section 11. Toxicological information

| Name | 0.0 | Route of exposure | Target organs |
|------------------|------------|-------------------|------------------------------|
| hydrogen sulfide | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------|------------|-------------------|---------------|
| carbon monoxide | Category 1 | - | - |

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : Contact with rapidly expanding gas may cause burns or frostbite.

Inhalation : No known significant effects or critical hazards.

Skin contact : Contact with rapidly expanding gas may cause burns or frostbite.

ingestion: As this product is a gas, refer to the inhalation section.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------|--|----------|
| hydrogen sulfide | Acute EC50 62 μg/l Fresh water | Crustaceans - Gammarus pseudolimnaeus | 2 days |
| | Acute LC50 2 μg/l Fresh water | Fish - Coregonus clupeaformis - Yolk-sac fry | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------------|----------------------|-----|------------|
| Nitrogen oxygen methane | 0.67 0.65 1.09 | - | low low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty pressure vessels should be returned to the supplier. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

| | DOT | TDG | Mexico | IMDG | IATA |
|-------------------------------|---|---|---|---|---|
| UN number | UN1956 | UN1956 | UN1956 | UN1956 | UN1956 |
| UN proper shipping name | COMPRESSED GAS, N.O.S. (nitrogen, oxygen) |
| Transport hazard class(es) | 2.2 | 2,2 | 2.2 | 2.2 | 2.2 |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |

Section 14. Transport information

Additional information

TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.13-2.17 (Class 2).

Explosive Limit and Limited Quantity Index 0.125

Passenger Carrying Road or Rail Index 75

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available. to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 311: hydrogen sulphide

Clean Air Act (CAA) 112 regulated flammable substances: methane

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602

Class | Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

| | | | SARA 302 | TPQ | SARA 304 F | RQ |
|------------------|-----------------|------|----------|-----------|------------|-----------|
| Name | % | EHS | (lbs) | (gallons) | (lbs) | (gallons) |
| hydrogen sulfide | 0.0001 - 0.2499 | Yes. | 500 | - | 100 | - |

SARA 304 RQ

: 80000 lbs / 36320 kg

SARA 311/312

Classification

: Refer to Section 2: Hazards Identification of this SDS for classification of substance.

State regulations

Massachusetts

: The following components are listed: NITROGEN; NITROGEN (LIQUIFIED); OXYGEN (LIQUID); METHANE; MARSH GAS

New York

: None of the components are listed.

New Jersey

: The following components are listed: NITROGEN; OXYGEN; METHANE

Pennsylvania

: The following components are listed: NITROGEN; OXYGEN; METHANE

California Prop. 65

🔼 WARNING: This product can expose you to Carbon monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Nonflammable Gas Mixture: Carbon Monoxide / Hydrogen Sulfide / Methane / Nitrogen / Oxygen | |
|--|--|
| Section 15. Regulatory information | |
| | |

| Ingredient name | | Maximum acceptable dosage level |
|-----------------|---|---------------------------------|
| Carbon monoxide | - | - |

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Viet Nam

Australia : All components are listed or exempted. Canada : All components are listed or exempted. China : All components are listed or exempted. : All components are listed or exempted. Europe : Japan inventory (CSCL): Not determined. Japan Japan inventory (ISHL): Not determined. **New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted. **Thailand** : All components are listed or exempted. : Not determined. Turkey **United States** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

: All components are listed or exempted.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Section 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

| Classification | Justification |
|---------------------------------------|-----------------------|
| GASES UNDER PRESSURE - Compressed gas | On basis of test data |

History

Date of printing

: 1/23/2022

Date of issue/Date of

: 1/23/2022

revision

Version

CAISIOII

Date of previous issue

: 10/14/2021 : 2

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

| | | , |
|--|--|---|
| | | |